

PRODUCT-DETAILS

003004

R25TL RIGID FEMALE FLANGE



General Information

Global Commercial Alias	003004
Product ID	7B003004
ABB Type Designation	R25TL RIGID FEMALE FLANGE
Catalog Description	R25TL RIGID FEMALE FLANGE

Additional Information

ABB Type Designation	R25TL RIGID FEMALE FLANGE
ATEX Certificate	NO
Bore Diameter	Maximum 2.6875 in Minimum 0.5 in
Bore Length	1.75 in
Bushing Size	2517
Bushing Type	Taper-Lock
Country of Origin	United States (US)
Coupling Component	Flange
Coupling Size	R25
Coupling Style	Rigid
Coupling Type	Metallic
Customs Tariff Number	84833032
Flange Material	Cast Iron
Global Commercial Alias	003004
Gross Volume	126.56 in ³
Gross Weight	4.726 kg

Horsepower Per 100 Rating	29.2 Hp
Invoice Description	R25TL RIGID FEMALE FLANGE
Lubrication	None
Made To Order	No
Maximum Speed	3545 r/min
Minimum Order Quantity	1 piece
Number of Bolts	5
Order Multiple	1 piece
Outside Diameter	7 in
Product Frame Size	R25
Product Name	DODGE COUPLINGS
Product Net Height	5.71 cm
Product Net Length	19.05 cm
Product Net Weight	4.726 kg
Product Net Width	19.05 cm
Product Type	Undefined
Quote Only	No
Rated Torque	18400 in-lb
Remarks	FEMALE FLANGE
Selling Unit of Measure	piece
Shaft Attachment	Bushed
Shaft Spacer	CLOSE-COUPLED
Shaft Spacing	Close Coupled
Size	R25
Spacer Distance	CLOSE-COUPLED
Stocked At (Warehouses)	China Alabama, United States Alaska, United States
Temperature Rating	Maximum 285 °F Minimum -100 °F
Tightening Torque	Central Bolt 900 in-lb
Torsional Rigidity	RIGID
WEEE B2C / B2B	Business To Business
WEEE Category	Product Not in WEEE Scope

Categories

Mechanical Power Transmission → Couplings → Metallic Couplings → Rigid → Taper-Lock Rigid

