

PRODUCT-DETAILS

009012

2 1/4 RIBBED COUPLING ASSEMBLY



General Information

Global Commercial Alias	009012
Product ID	7B009012
ABB Type Designation	2 1/4 RIBBED COUPLING ASSEMBLY
Catalog Description	2 1/4 RIBBED COUPLING ASSEMBLY

Additional Information

ABB Type Designation	2 1/4 RIBBED COUPLING ASSEMBLY
ATEX Certificate	NO
Bore Diameter	Actual 2.25 in
Bore Fit	Interference
Bore Length	8.625 in
Bore Tolerance Standard	Custom
Country of Origin	United States (US)
Coupling Size	2.25
Coupling Style	Rigid
Coupling Type	Metallic
Customs Tariff Number	84839089
Global Commercial Alias	009012
Gross Volume	0 in ³
Gross Weight	12.939 kg
Horsepower Per 100 Rating	21.3 Hp
Invoice Description	2 1/4 RIBBED COUPLING ASSEMBLY

Lubrication	None
Made To Order	No
Material	CastIron
Maximum Speed	3180 r/min
Minimum Order Quantity	1 piece
Number of Bolts	4
Order Multiple	1 piece
Outside Diameter	6 in
Product Name	DODGE COUPLINGS
Product Net Height	20.32 cm
Product Net Length	20.32 cm
Product Net Weight	12.939 kg
Product Net Width	73.66 cm
Product Type	Undefined
Quote Only	No
Rated Torque	13400 in-lb
Selling Unit of Measure	piece
Shaft Attachment	Bored To Size
Shaft Diameter	2 1/4 in
Shaft Spacer	CLOSE-COUPLED
Shaft Spacing	Close Coupled
Size	2-1/4
Spacer Distance	CLOSE-COUPLED
Stocked At (Warehouses)	China Alabama, United States Alaska, United States
Temperature Rating	Maximum 285 °F Minimum -100 °F
Tightening Torque	Central Bolt 1200 in-lb
Torsional Rigidity	RIGID
WEEE B2C / B2B	Business To Business
WEEE Category	Product Not in WEEE Scope

Categories

Mechanical Power Transmission → Couplings → Metallic Couplings → Rigid → Ribbed Rigid

