

PRODUCT-DETAILS

**009015**

# 2 7/16 RIBBED COUPLING ASSEMBLY



## General Information

|                         |                                 |
|-------------------------|---------------------------------|
| Global Commercial Alias | 009015                          |
| Product ID              | 7B009015                        |
| ABB Type Designation    | 2 7/16 RIBBED COUPLING ASSEMBLY |
| Catalog Description     | 2 7/16 RIBBED COUPLING ASSEMBLY |

## Additional Information

|                           |                                 |
|---------------------------|---------------------------------|
| ABB Type Designation      | 2 7/16 RIBBED COUPLING ASSEMBLY |
| ATEX Certificate          | NO                              |
| Bore Diameter             | Actual 2.4375 in                |
| Bore Fit                  | Interference                    |
| Bore Length               | 9.6875 in                       |
| Bore Tolerance Standard   | Custom                          |
| Country of Origin         | United States (US)              |
| Coupling Size             | 2.4375                          |
| Coupling Style            | Rigid                           |
| Coupling Type             | Metallic                        |
| Customs Tariff Number     | 84833032                        |
| Global Commercial Alias   | 009015                          |
| Gross Volume              | 0 in <sup>3</sup>               |
| Gross Weight              | 18.16 kg                        |
| Horsepower Per 100 Rating | 27.1 Hp                         |
| Invoice Description       | 2 7/16 RIBBED COUPLING ASSEMBLY |

|                            |                                                          |
|----------------------------|----------------------------------------------------------|
| Lubrication                | None                                                     |
| Made To Order              | No                                                       |
| Material                   | CastIron                                                 |
| Maximum Speed              | 2965 r/min                                               |
| Minimum Order Quantity     | 1 piece                                                  |
| Number of Bolts            | 6                                                        |
| Order Multiple             | 1 piece                                                  |
| Outside Diameter           | 6.4375 in                                                |
| Product Name               | DODGE COUPLINGS                                          |
| Product Net Height         | 17.78 cm                                                 |
| Product Net Length         | 27.94 cm                                                 |
| Product Net Weight         | 18.16 kg                                                 |
| Product Net Width          | 96.52 cm                                                 |
| Product Type               | Undefined                                                |
| Quote Only                 | No                                                       |
| Rated Torque               | 17100 in-lb                                              |
| Selling Unit of Measure    | piece                                                    |
| Shaft Attachment           | Bored To Size                                            |
| Shaft Diameter             | 2 7/16 in                                                |
| Shaft Spacer               | CLOSE-COUPLED                                            |
| Shaft Spacing              | Close Coupled                                            |
| Size                       | 2-7/16                                                   |
| Spacer Distance            | CLOSE-COUPLED                                            |
| Stocked At<br>(Warehouses) | China<br>Alabama, United States<br>Alaska, United States |
| Temperature Rating         | Maximum 285 °F<br>Minimum -100 °F                        |
| Tightening Torque          | Central Bolt 1200 in-lb                                  |
| Torsional Rigidity         | RIGID                                                    |
| WEEE B2C / B2B             | Business To Business                                     |
| WEEE Category              | Product Not in WEEE Scope                                |

---

## Categories

---

Mechanical Power Transmission → Couplings → Metallic Couplings → Rigid → Ribbed Rigid

