

PRODUCT-DETAILS

009050

5-1/2 RIBBED RIGID CPLG



General Information

Global Commercial Alias	009050
Product ID	7B009050
ABB Type Designation	5-1/2 RIBBED RIGID CPLG
Catalog Description	5-1/2 RIBBED RIGID CPLG

Additional Information

ABB Type Designation	5-1/2 RIBBED RIGID CPLG
ATEX Certificate	NO
Bore Diameter	Actual 5.5 in
Bore Fit	Interference
Bore Length	20.375 in
Bore Tolerance Standard	Custom
Country of Origin	United States (US)
Coupling Size	5.5
Coupling Style	Rigid
Coupling Type	Metallic
Customs Tariff Number	84839089
Global Commercial Alias	009050
Gross Weight	204.3 kg
Horsepower Per 100 Rating	311 Hp
Invoice Description	5-1/2 RIBBED RIGID CPLG
Lubrication	None

Made To Order	No
Material	CastIron
Maximum Speed	1390 r/min
Minimum Order Quantity	1 piece
Number of Bolts	8
Order Multiple	1 piece
Outside Diameter	13.75 in
Product Name	DODGE COUPLINGS
Product Net Height	0 cm
Product Net Length	0 cm
Product Net Weight	204.3 kg
Product Net Width	0 cm
Product Type	Undefined
Quote Only	No
Rated Torque	196000 in·lb
Selling Unit of Measure	piece
Shaft Attachment	Bored To Size
Shaft Diameter	5 1/2 in
Shaft Spacer	CLOSE-COUPLED
Shaft Spacing	Close Coupled
Size	5-1/2
Spacer Distance	CLOSE-COUPLED
Stocked At (Warehouses)	China Alabama, United States Alaska, United States
Temperature Rating	Maximum 285 °F Minimum -100 °F
Tightening Torque	Central Bolt 4200 in·lb
Torsional Rigidity	RIGID
WEEE B2C / B2B	Business To Business
WEEE Category	Product Not in WEEE Scope

Categories

Mechanical Power Transmission → Couplings → Metallic Couplings → Rigid → Ribbed Rigid

