

PRODUCT-DETAILS

009054

6 RIBBED RIGID CPLG



General Information

Global Commercial Alias	009054
Product ID	7B009054
ABB Type Designation	6 RIBBED RIGID CPLG
Catalog Description	6 RIBBED RIGID CPLG

Additional Information

ABB Type Designation	6 RIBBED RIGID CPLG
ATEX Certificate	NO
Bore Diameter	Actual 6 in
Bore Fit	Interference
Bore Length	20.75 in
Bore Tolerance Standard	Custom
Country of Origin	United States (US)
Coupling Size	6
Coupling Style	Rigid
Coupling Type	Metallic
Customs Tariff Number	84839089
Global Commercial Alias	009054
Gross Weight	204.3 kg
Horsepower Per 100 Rating	404.6 Hp
Invoice Description	6 RIBBED RIGID CPLG
Lubrication	None

Made To Order	No
Material	CastIron
Maximum Speed	1365 r/min
Minimum Order Quantity	1 piece
Number of Bolts	6
Order Multiple	1 piece
Outside Diameter	14 in
Product Name	DODGE COUPLINGS
Product Net Height	0 cm
Product Net Length	0 cm
Product Net Weight	204.3 kg
Product Net Width	0 cm
Product Type	Undefined
Quote Only	No
Rated Torque	255000 in·lb
Selling Unit of Measure	piece
Shaft Attachment	Bored To Size
Shaft Diameter	6 in
Shaft Spacer	CLOSE-COUPLED
Shaft Spacing	Close Coupled
Size	6
Spacer Distance	CLOSE-COUPLED
Stocked At (Warehouses)	China Alabama, United States Alaska, United States
Temperature Rating	Maximum 285 °F Minimum -100 °F
Tightening Torque	Central Bolt 6000 in·lb
Torsional Rigidity	RIGID
WEEE B2C / B2B	Business To Business
WEEE Category	Product Not in WEEE Scope

Categories

Mechanical Power Transmission → Couplings → Metallic Couplings → Rigid → Ribbed Rigid

