

PRODUCT-DETAILS

011268

PH116 PARA-FLEX NEOPRENE ELEMENT



General Information

Global Commercial Alias	011268
Product ID	7B011268
ABB Type Designation	PH116 PARA-FLEX NEOPRENE ELEMENT
Catalog Description	PH116 PARA-FLEX NEOPRENE ELEMENT

Additional Information

ABB Type Designation	PH116 PARA-FLEX NEOPRENE ELEMENT
ATEX Certificate	YES
Angular Misalignment	1 °
Axial Misalignment	0.1875 in
Country of Origin	United States (US)
Coupling Component	Element
Coupling Size	PH116
Coupling Style	Tire
Coupling Type	Elastomeric
Customs Tariff Number	84833032
Element Material	Neoprene
Element Style	High Speed
Global Commercial Alias	011268
Gross Volume	1642.17 in ³
Gross Weight	1.298 kg
Horsepower Per 100 Rating	7.1 Hp

Invoice Description	PH116 PARA-FLEX NEOPRENE ELEMENT
Lubrication	None
Made To Order	No
Maximum Speed	4050 r/min
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Outside Diameter	12.3125 in
Parallel Misalignment	0.0625 in
Product Frame Size	PH/PF 116
Product Name	DODGE COUPLINGS
Product Net Height	13.34 cm
Product Net Length	43.51 cm
Product Net Weight	1.298 kg
Product Net Width	46.38 cm
Product Series	HIGHSPEED (PH)
Product Type	Undefined
Quote Only	No
Rated Torque	4470 in-lb
Remarks	ELEMENT
Selling Unit of Measure	piece
Shaft Spacer	CLOSE-COUPLED
Shaft Spacing	Close Coupled
Size	PH116
Spacer Distance	CLOSE-COUPLED
Stocked At (Warehouses)	China Alabama, United States Alaska, United States
Temperature Rating	Maximum 180 °F Minimum -45 °F
Torsional Rigidity	FLEXIBLE
Torsional Stiffness	2182 in-lb/degree
WEEE B2C / B2B	Business To Business
WEEE Category	Product Not in WEEE Scope

Categories

Mechanical Power Transmission → Couplings → Elastomeric Couplings → Tire (Para-Flex)

