



## PRODUCT-DETAILS

# 011304

## PX140 PARA-FLEX NEOPRENE ELEMENT

### General Information

|                         |                                  |
|-------------------------|----------------------------------|
| Global Commercial Alias | 011304                           |
| Product ID              | 7B011304                         |
| ABB Type Designation    | PX140 PARA-FLEX NEOPRENE ELEMENT |
| Catalog Description     | PX140 PARA-FLEX NEOPRENE ELEMENT |

### Additional Information

|                           |                                  |
|---------------------------|----------------------------------|
| ABB Type Designation      | PX140 PARA-FLEX NEOPRENE ELEMENT |
| ATEX Certificate          | YES                              |
| Angular Misalignment      | 4 °                              |
| Axial Misalignment        | 0.3125 in                        |
| Country of Origin         | United States (US)               |
| Coupling Component        | Element                          |
| Coupling Size             | PX140                            |
| Coupling Style            | Tire                             |
| Coupling Type             | Elastomeric                      |
| Customs Tariff Number     | 84833032                         |
| Element Material          | Neoprene                         |
| Element Style             | Standard                         |
| Global Commercial Alias   | 011304                           |
| Gross Weight              | 2.624 kg                         |
| Horsepower Per 100 Rating | 44 Hp                            |
| Invoice Description       | PX140 PARA-FLEX NEOPRENE ELEMENT |
| Lubrication               | None                             |
| Made To Order             | No                               |
| Maximum Speed             | 1840 r/min                       |
| Minimum Order Quantity    | 1 piece                          |
| Order Multiple            | 1 piece                          |
| Outside Diameter          | 14.125 in                        |
| Parallel Misalignment     | 0.125 in                         |
| Product Frame Size        | PX140                            |
| Product Name              | DODGE COUPLINGS                  |
| Product Net Height        | 10.79 cm                         |
| Product Net Length        | 38.73 cm                         |
| Product Net Weight        | 2.624 kg                         |
| Product Net Width         | 41.91 cm                         |
| Product Type              | Undefined                        |

|                            |                                                          |
|----------------------------|----------------------------------------------------------|
| Quote Only                 | No                                                       |
| Rated Torque               | 27590 in-lb                                              |
| Remarks                    | ELEMENT                                                  |
| Selling Unit of Measure    | piece                                                    |
| Shaft Spacing              | Close Coupled                                            |
| Size                       | PX140                                                    |
| Stocked At<br>(Warehouses) | China<br>Alabama, United States<br>Alaska, United States |
| Temperature Rating         | Maximum 180 °F<br>Minimum -45 °F                         |
| Torsional Rigidity         | FLEXIBLE                                                 |
| Torsional Stiffness        | 8296 in-lb/degree                                        |
| WEEE B2C / B2B             | Business To Business                                     |
| WEEE Category              | Product Not in WEEE Scope                                |

---

**Categories**

---

Mechanical Power Transmission → Couplings → Elastomeric Couplings → Tire (Para-Flex)