

PRODUCT-DETAILS

**013006**

**PXM 110 PX ELEMENT**



### General Information

|                         |                    |
|-------------------------|--------------------|
| Global Commercial Alias | 013006             |
| Product ID              | 7B013006           |
| ABB Type Designation    | PXM 110 PX ELEMENT |
| Catalog Description     | PXM 110 PX ELEMENT |

### Additional Information

|                           |                    |
|---------------------------|--------------------|
| ABB Type Designation      | PXM 110 PX ELEMENT |
| Angular Misalignment      | 4 °                |
| Axial Misalignment        | 0.3125 in          |
| Country of Origin         | United States (US) |
| Coupling Component        | Element            |
| Coupling Size             | PX110              |
| Coupling Style            | Tire               |
| Coupling Type             | Elastomeric        |
| Customs Tariff Number     | 84833032           |
| Element Material          | Natural Rubber     |
| Global Commercial Alias   | 013006             |
| Gross Weight              | 1.634 kg           |
| Horsepower Per 100 Rating | 12.3 Hp            |
| Invoice Description       | PXM 110 PX ELEMENT |
| Lubrication               | None               |
| Made To Order             | No                 |

|                            |                                                          |
|----------------------------|----------------------------------------------------------|
| Maximum Speed              | 2300 r/min                                               |
| Minimum Order Quantity     | 1 piece                                                  |
| Order Multiple             | 1 piece                                                  |
| Outside Diameter           | 11 in                                                    |
| Parallel Misalignment      | 0.125 in                                                 |
| Product Name               | DODGE COUPLINGS                                          |
| Product Net Height         | 0 cm                                                     |
| Product Net Length         | 0 cm                                                     |
| Product Net Weight         | 1.634 kg                                                 |
| Product Net Width          | 0 cm                                                     |
| Product Type               | Undefined                                                |
| Quote Only                 | No                                                       |
| Rated Torque               | 7750 in-lb                                               |
| Selling Unit of Measure    | piece                                                    |
| Shaft Spacing              | Close Coupled                                            |
| Size                       | PXM110                                                   |
| Stocked At<br>(Warehouses) | China<br>Alabama, United States<br>Alaska, United States |
| Temperature Rating         | Maximum 180 °F<br>Minimum -45 °F                         |
| Torsional Stiffness        | 2420 in-lb/degree                                        |
| WEEE B2C / B2B             | Business To Business                                     |
| WEEE Category              | Product Not in WEEE Scope                                |

Categories

Mechanical Power Transmission → Couplings → Elastomeric Couplings → Tire (Para-Flex)

