



PRODUCT-DETAILS

013122

DGF 2.5 FLEX HUB RSB X 1.44

General Information

Global Commercial Alias	013122
Product ID	7B013122
ABB Type Designation	DGF 2.5 FLEX HUB RSB X 1.44
Catalog Description	DGF 2.5 FLEX HUB RSB X 1.44

Additional Information

ABB Type Designation	DGF 2.5 FLEX HUB RSB X 1.44
ATEX Certificate	NO
Angular Misalignment	1.5 °
Bore Diameter	Maximum 3.375 in Minimum 1.4375 in
Bore Length	3.0313 in
Country of Origin	United States (US)
Coupling Component	Hub
Coupling Size	2.5
Coupling Style	Gear
Coupling Type	Metallic
Customs Tariff Number	84833032
Global Commercial Alias	013122
Gross Volume	178.06 in ³
Gross Weight	6.992 kg
Horsepower Per 100 Rating	90 Hp
Invoice Description	DGF 2.5 FLEX HUB RSB X 1.44
Lubrication	Grease
Made To Order	No
Material	Steel
Maximum Speed	4400 r/min
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Outside Diameter	4.625 in
Parallel Misalignment	0.105 in
Product Frame Size	DGF 2.5
Product Name	DODGE COUPLINGS
Product Net Height	10.59 cm
Product Net Length	16.41 cm
Product Net Weight	6.992 kg

Product Net Width	16.79 cm
Product Type	Undefined
Quote Only	No
Rated Torque	56700 in-lb
Remarks	FLEX HUB
Selling Unit of Measure	piece
Shaft Attachment	Rough Bore
Shaft Spacer	CLOSE-COUPLED
Shaft Spacing	Close Coupled
Size	2.5
Spacer Distance	CLOSE-COUPLED
Stocked At (Warehouses)	China Alabama, United States Alaska, United States
Temperature Rating	Maximum 250 °F Minimum -30 °F
Torsional Rigidity	FLEXIBLE
WEEE B2C / B2B	Business To Business
WEEE Category	Product Not in WEEE Scope

Categories

Mechanical Power Transmission → Couplings → Metallic Couplings → Gear