



## PRODUCT-DETAILS

# 013163

## DGF 9.0 EXPOSED BOLT SLEEVE

### General Information

|                         |                             |
|-------------------------|-----------------------------|
| Global Commercial Alias | 013163                      |
| Product ID              | 7B013163                    |
| ABB Type Designation    | DGF 9.0 EXPOSED BOLT SLEEVE |
| Catalog Description     | DGF 9.0 EXPOSED BOLT SLEEVE |

### Additional Information

|                           |                             |
|---------------------------|-----------------------------|
| ABB Type Designation      | DGF 9.0 EXPOSED BOLT SLEEVE |
| ATEX Certificate          | NO                          |
| Angular Misalignment      | 0.75 °                      |
| Country of Origin         | United States (US)          |
| Coupling Component        | Sleeve                      |
| Coupling Size             | 9                           |
| Coupling Style            | Gear                        |
| Coupling Type             | Metallic                    |
| Customs Tariff Number     | 84839089                    |
| Flange Material           | Steel                       |
| Global Commercial Alias   | 013163                      |
| Gross Weight              | 192.95 kg                   |
| Horsepower Per 100 Rating | 2899 Hp                     |
| Invoice Description       | DGF 9.0 EXPOSED BOLT SLEEVE |
| Lubrication               | Grease                      |
| Made To Order             | No                          |
| Maximum Speed             | 1750 r/min                  |
| Minimum Order Quantity    | 1 piece                     |
| Order Multiple            | 1 piece                     |
| Outside Diameter          | 26 in                       |
| Parallel Misalignment     | 0.165 in                    |
| Product Frame Size        | DGF 9.0                     |
| Product Name              | DODGE COUPLINGS             |
| Product Net Height        | 0 cm                        |
| Product Net Length        | 0 cm                        |
| Product Net Weight        | 192.95 kg                   |
| Product Net Width         | 0 cm                        |
| Product Type              | Undefined                   |
| Quote Only                | No                          |
| Rated Torque              | 1827000 in-lb               |

|                         |                                  |
|-------------------------|----------------------------------|
| Remarks                 | FLEX SLEEVE                      |
| Selling Unit of Measure | piece                            |
| Shaft Spacer            | CLOSE-COUPLED                    |
| Shaft Spacing           | Close Coupled                    |
| Spacer Distance         | CLOSE-COUPLED                    |
| Stocked At              | China                            |
| (Warehouses)            | Alabama, United States           |
| Temperature Rating      | Maximum 250 °F<br>Minimum -30 °F |
| Torsional Rigidity      | FLEXIBLE                         |
| WEEE B2C / B2B          | Business To Business             |
| WEEE Category           | Product Not in WEEE Scope        |

---

**Categories**

---

Mechanical Power Transmission → Couplings → Metallic Couplings → Gear