



## PRODUCT-DETAILS

# 013166

## DGF 7.0 SD FLEX HUB

### General Information

|                         |                     |
|-------------------------|---------------------|
| Global Commercial Alias | 013166              |
| Product ID              | 7B013166            |
| ABB Type Designation    | DGF 7.0 SD FLEX HUB |
| Catalog Description     | DGF 7.0 SD FLEX HUB |

### Additional Information

|                           |                                 |
|---------------------------|---------------------------------|
| ABB Type Designation      | DGF 7.0 SD FLEX HUB             |
| ATEX Certificate          | NO                              |
| Angular Misalignment      | 0.75 °                          |
| Bore Diameter             | Maximum 9.75 in<br>Minimum 5 in |
| Bore Length               | 8.6875 in                       |
| Country of Origin         | United States (US)              |
| Coupling Component        | Hub                             |
| Coupling Size             | 7                               |
| Coupling Style            | Gear                            |
| Coupling Type             | Metallic                        |
| Customs Tariff Number     | 84833032                        |
| Global Commercial Alias   | 013166                          |
| Gross Weight              | 133.93 kg                       |
| Horsepower Per 100 Rating | 1600 Hp                         |
| Invoice Description       | DGF 7.0 SD FLEX HUB             |
| Lubrication               | Grease                          |
| Made To Order             | No                              |
| Material                  | Steel                           |
| Maximum Speed             | 2000 r/min                      |
| Minimum Order Quantity    | 1 piece                         |
| Order Multiple            | 1 piece                         |
| Outside Diameter          | 13 in                           |
| Parallel Misalignment     | 0.135 in                        |
| Product Frame Size        | DGF 7.0                         |
| Product Name              | DODGE COUPLINGS                 |
| Product Net Height        | 0 cm                            |
| Product Net Length        | 0 cm                            |
| Product Net Weight        | 133.93 kg                       |
| Product Net Width         | 0 cm                            |

|                            |                                                          |
|----------------------------|----------------------------------------------------------|
| Product Type               | Undefined                                                |
| Quote Only                 | No                                                       |
| Rated Torque               | 1008400 in-lb                                            |
| Remarks                    | FLEX HUB                                                 |
| Selling Unit of Measure    | piece                                                    |
| Shaft Attachment           | Rough Bore                                               |
| Shaft Spacer               | CLOSE-COUPLED                                            |
| Shaft Spacing              | Close Coupled                                            |
| Spacer Distance            | CLOSE-COUPLED                                            |
| Stocked At<br>(Warehouses) | China<br>Alabama, United States<br>Alaska, United States |
| Temperature Rating         | Maximum 250 °F<br>Minimum -30 °F                         |
| Torsional Rigidity         | FLEXIBLE                                                 |
| WEEE B2C / B2B             | Business To Business                                     |
| WEEE Category              | Product Not in WEEE Scope                                |

Categories

Mechanical Power Transmission → Couplings → Metallic Couplings → Gear