

PRODUCT-DETAILS

**016508**

**RAPTOR 120HCB 150MM P7 INT FIT**



**General Information**

|                         |                                |
|-------------------------|--------------------------------|
| Global Commercial Alias | 016508                         |
| Product ID              | 7B016508                       |
| ABB Type Designation    | RAPTOR 120HCB 150MM P7 INT FIT |
| Catalog Description     | RAPTOR 120HCB 150MM P7 INT FIT |

**Additional Information**

|                           |                                |
|---------------------------|--------------------------------|
| ABB Type Designation      | RAPTOR 120HCB 150MM P7 INT FIT |
| Angular Misalignment      | 1.5 °                          |
| Axial Misalignment        | 0.3125 in                      |
| Bore Diameter             | Actual 150 mm                  |
| Bore Fit                  | Interference                   |
| Bore Length               | 6 in                           |
| Bore Tolerance Standard   | ISO R775                       |
| Country of Origin         | United States (US)             |
| Coupling Component        | Hub                            |
| Coupling Size             | 120                            |
| Coupling Style            | Split-Tire                     |
| Coupling Type             | Elastomeric                    |
| Customs Tariff Number     | 84839089                       |
| Global Commercial Alias   | 016508                         |
| Gross Weight              | 87.077 kg                      |
| Horsepower Per 100 Rating | 270 Hp                         |

|                            |                                                          |
|----------------------------|----------------------------------------------------------|
| ISO Fit Standard           | P7                                                       |
| Invoice Description        | RAPTOR 120HCB 150MM P7 INT FIT                           |
| Lubrication                | None                                                     |
| Made To Order              | No                                                       |
| Material                   | Steel                                                    |
| Maximum Speed              | 1800 r/min                                               |
| Minimum Order Quantity     | 1 piece                                                  |
| Order Multiple             | 1 piece                                                  |
| Outside Diameter           | 17.63 in                                                 |
| Parallel Misalignment      | 0.1875 in                                                |
| Product Name               | DODGE COUPLINGS                                          |
| Product Net Height         | 0 cm                                                     |
| Product Net Length         | 0 cm                                                     |
| Product Net Weight         | 87.077 kg                                                |
| Product Net Width          | 0 cm                                                     |
| Product Type               | Undefined                                                |
| Quote Only                 | No                                                       |
| Rated Torque               | 170170 in-lb                                             |
| Selling Unit of Measure    | piece                                                    |
| Shaft Attachment           | Bored To Size                                            |
| Shaft Spacing              | Close Coupled<br>Spacer                                  |
| Stocked At<br>(Warehouses) | China<br>Alabama, United States<br>Alaska, United States |
| Temperature Rating         | Maximum 220 °F<br>Minimum -45 °F                         |

Categories

Mechanical Power Transmission → Couplings → Elastomeric Couplings → Split-Tire (Raptor)

