

PRODUCT-DETAILS

**016888**

No Description Available



### General Information

|                         |                          |
|-------------------------|--------------------------|
| Global Commercial Alias | 016888                   |
| Product ID              | 7B016888                 |
| ABB Type Designation    | RAPTOR 4HCBM 32MM H7     |
| Catalog Description     | No Description Available |

### Additional Information

|                           |                      |
|---------------------------|----------------------|
| ABB Type Designation      | RAPTOR 4HCBM 32MM H7 |
| Angular Misalignment      | 4 °                  |
| Axial Misalignment        | 0.3125 in            |
| Bore Diameter             | Actual 32 mm         |
| Bore Fit                  | Transitional         |
| Bore Length               | 1.68 in              |
| Bore Tolerance Standard   | ISO R775             |
| Country of Origin         | United States (US)   |
| Coupling Component        | Hub                  |
| Coupling Size             | 4                    |
| Coupling Style            | Split-Tire           |
| Coupling Type             | Elastomeric          |
| Customs Tariff Number     | 84833032             |
| Global Commercial Alias   | 016888               |
| Gross Weight              | 0.726 kg             |
| Horsepower Per 100 Rating | 0.89 Hp              |

|                            |                                                          |
|----------------------------|----------------------------------------------------------|
| ISO Fit Standard           | H7                                                       |
| Lubrication                | None                                                     |
| Made To Order              | No                                                       |
| Material                   | Steel                                                    |
| Maximum Speed              | 7500 r/min                                               |
| Minimum Order Quantity     | 1 piece                                                  |
| Order Multiple             | 1 piece                                                  |
| Outside Diameter           | 2.6 in                                                   |
| Parallel Misalignment      | 0.1875 in                                                |
| Product Name               | DODGE COUPLINGS                                          |
| Product Net Height         | 0 cm                                                     |
| Product Net Length         | 0 cm                                                     |
| Product Net Weight         | 0.726 kg                                                 |
| Product Net Width          | 0 cm                                                     |
| Product Type               | Undefined                                                |
| Quote Only                 | No                                                       |
| Rated Torque               | 558 in-lb                                                |
| Selling Unit of Measure    | piece                                                    |
| Shaft Attachment           | Bored To Size                                            |
| Shaft Spacing              | Close Coupled<br>Spacer                                  |
| Stocked At<br>(Warehouses) | China<br>Alabama, United States<br>Alaska, United States |
| Temperature Rating         | Maximum 220 °F<br>Minimum -45 °F                         |

Categories

Mechanical Power Transmission → Couplings → Elastomeric Couplings → Split-Tire (Raptor)

