



## PRODUCT-DETAILS

# 017133

## No Description Available

### General Information

|                         |                            |
|-------------------------|----------------------------|
| Global Commercial Alias | 017133                     |
| Product ID              | 7B017133                   |
| ABB Type Designation    | RAPTOR E40 ARMORED ELEMENT |
| Catalog Description     | No Description Available   |

### Additional Information

|                             |                                    |
|-----------------------------|------------------------------------|
| ABB Type Designation        | RAPTOR E40 ARMORED ELEMENT         |
| Angular Misalignment        | 3 °                                |
| Axial Misalignment          | 0.3125 in                          |
| Country of Origin           | United States (US)                 |
| Coupling Component          | Element                            |
| Coupling Size               | 40                                 |
| Coupling Style              | Split-Tire                         |
| Coupling Type               | Elastomeric                        |
| Customs Tariff Number       | 84833032                           |
| Distance Between Shaft Ends | Maximum 3.29 in<br>Minimum 0.43 in |
| Element Material            | Natural Rubber                     |
| Global Commercial Alias     | 017133                             |
| Gross Weight                | 3.223 kg                           |
| Horsepower Per 100 Rating   | 8.73 Hp                            |
| Lubrication                 | None                               |
| Made To Order               | No                                 |
| Maximum Speed               | 5000 r/min                         |
| Minimum Order Quantity      | 1 piece                            |
| Number of Bolts             | 16                                 |
| Order Multiple              | 1 piece                            |
| Outside Diameter            | 9.5 in                             |
| Parallel Misalignment       | 0.1875 in                          |
| Product Name                | DODGE COUPLINGS                    |
| Product Net Height          | 17.78 cm                           |
| Product Net Length          | 34.29 cm                           |
| Product Net Weight          | 3.223 kg                           |
| Product Net Width           | 33.02 cm                           |
| Product Type                | Undefined                          |
| Quote Only                  | No                                 |

|                            |                                                          |
|----------------------------|----------------------------------------------------------|
| Rated Torque               | 5504 in-lb                                               |
| Selling Unit of Measure    | piece                                                    |
| Shaft Spacing              | Close Coupled                                            |
| Stocked At<br>(Warehouses) | China<br>Alabama, United States<br>Alaska, United States |
| Temperature Rating         | Maximum 220 °F<br>Minimum -45 °F                         |
| Tightening Torque          | Central Bolt 502 in-lb                                   |
| Torsional Stiffness        | 440 in-lb/degree                                         |

---

**Categories**

---

Mechanical Power Transmission → Couplings → Elastomeric Couplings → Split-Tire (Raptor)