

PRODUCT-DETAILS

**099106**

**FB4016 X 1 1/8 CHAIN CPLG FLG**



### General Information

|                         |                               |
|-------------------------|-------------------------------|
| Global Commercial Alias | 099106                        |
| Product ID              | 7B099106                      |
| ABB Type Designation    | FB4016 X 1 1/8 CHAIN CPLG FLG |
| Catalog Description     | FB4016 X 1 1/8 CHAIN CPLG FLG |

### Additional Information

|                         |                                  |
|-------------------------|----------------------------------|
| ABB Type Designation    | FB4016 X 1 1/8 CHAIN CPLG FLG    |
| ATEX Certificate        | NO                               |
| Angular Misalignment    | 2 °                              |
| Axial Misalignment      | 0.3 in                           |
| Bore Diameter           | Actual 1.125 in                  |
| Bore Fit                | Clearance                        |
| Bore Length             | 1.13 in                          |
| Bore Tolerance Standard | AGMA 9002                        |
| Country of Origin       | United States (US)<br>China (CN) |
| Coupling Component      | Flange                           |
| Coupling Size           | 4016                             |
| Coupling Style          | Chain                            |
| Coupling Type           | Metallic                         |
| Customs Tariff Number   | 84839089                         |
| Flange Material         | Steel                            |
| Global Commercial Alias | 099106                           |

|                            |                                                          |
|----------------------------|----------------------------------------------------------|
| Gross Weight               | 0.368 kg                                                 |
| Invoice Description        | FB4016 X 1 1/8 CHAIN CPLG FLG                            |
| Lubrication                | Grease                                                   |
| Made To Order              | No                                                       |
| Maximum Speed              | With Cover 5000 r/min<br>Without Cover 875 r/min         |
| Minimum Order Quantity     | 1 piece                                                  |
| Order Multiple             | 1 piece                                                  |
| Outside Diameter           | 1.97 in                                                  |
| Parallel Misalignment      | 0.015 in                                                 |
| Product Frame Size         | 4016                                                     |
| Product Name               | DODGE COUPLINGS                                          |
| Product Net Height         | 3.17 cm                                                  |
| Product Net Length         | 7.62 cm                                                  |
| Product Net Weight         | 0.368 kg                                                 |
| Product Net Width          | 7.62 cm                                                  |
| Product Type               | Undefined                                                |
| Quote Only                 | No                                                       |
| Remarks                    | FLANGE                                                   |
| Selling Unit of Measure    | piece                                                    |
| Shaft Attachment           | Bored To Size                                            |
| Shaft Diameter             | 1 1/8 in                                                 |
| Shaft Spacer               | CLOSE-COUPLED                                            |
| Shaft Spacing              | Close Coupled                                            |
| Size                       | 4012                                                     |
| Spacer Distance            | CLOSE-COUPLED                                            |
| Stocked At<br>(Warehouses) | China<br>Alabama, United States<br>Alaska, United States |
| Temperature Rating         | Maximum 225 °F<br>Minimum -30 °F                         |
| Torsional Rigidity         | FLEXIBLE                                                 |
| WEEE B2C / B2B             | Business To Business                                     |
| WEEE Category              | Product Not in WEEE Scope                                |

Categories

Mechanical Power Transmission → Couplings → Metallic Couplings → Chain

