

PRODUCT-DETAILS

# 107912

## A59 BELT



### General Information

|                         |          |
|-------------------------|----------|
| Global Commercial Alias | 107912   |
| Product ID              | 7B107912 |
| ABB Type Designation    | A59 BELT |
| Catalog Description     | A59 BELT |

### Additional Information

|                                |                                  |
|--------------------------------|----------------------------------|
| ABB Type Designation           | A59 BELT                         |
| Belt Length                    | Datum 60.3 in<br>Outside 61 in   |
| Belt Reinforcement<br>Material | Length Stabilized Polyester Cord |
| Belt Type                      | V-Belt                           |
| Belt Width                     | 0.3125 in                        |
| Country of Origin              | United States (US)               |
| Customs Tariff Number          | 40103100                         |
| Global Commercial Alias        | 107912                           |
| Gross Weight                   | 0.182 kg                         |
| Invoice Description            | A59 BELT                         |
| Made To Order                  | No                               |
| Material                       | Neoprene Rubber Body             |
| Minimum Order Quantity         | 1 piece                          |
| Order Multiple                 | 1 piece                          |
| Product Name                   | DODGE BELTS                      |

|                            |                                                          |
|----------------------------|----------------------------------------------------------|
| Product Net Height         | 1.91 cm                                                  |
| Product Net Length         | 21.59 cm                                                 |
| Product Net Weight         | 0.182 kg                                                 |
| Product Net Width          | 21.59 cm                                                 |
| Product Type               | Undefined                                                |
| Profile Type               | AP                                                       |
| Quote Only                 | No                                                       |
| Selling Unit of Measure    | piece                                                    |
| Standards                  | RMA                                                      |
| Stocked At<br>(Warehouses) | China<br>Alabama, United States<br>Alaska, United States |
| Temperature Range          | Maximum 140 °F<br>Minimum -30 °F                         |
| V-Belt Design              | Single                                                   |
| V-Belt Sides               | Single                                                   |
| WEEE B2C / B2B             | Business To Business                                     |
| WEEE Category              | Product Not in WEEE Scope                                |
| V-Belt Profiles            | Classical A                                              |
| Static Conductive          | Yes                                                      |
| Belt Height                | 0.5 in                                                   |
| Number of Bands            | 1                                                        |
| Oil Resistance             | Good                                                     |
| V-Belt Construction        | Wrapped                                                  |

---

**Categories**

---

Mechanical Power Transmission → Belted Drives → V-Belts → Classical (A, B, C, D) → Single

