

PRODUCT-DETAILS

# 108710

## BX93 BELT



### General Information

|                         |           |
|-------------------------|-----------|
| Global Commercial Alias | 108710    |
| Product ID              | 7B108710  |
| ABB Type Designation    | BX93 BELT |
| Catalog Description     | BX93 BELT |

### Additional Information

|                                |                                  |
|--------------------------------|----------------------------------|
| ABB Type Designation           | BX93 BELT                        |
| Belt Length                    | Datum 94.8 in<br>Outside 96 in   |
| Belt Reinforcement<br>Material | Length Stabilized Polyester Cord |
| Belt Type                      | V-Belt                           |
| Belt Width                     | 0.65625 in                       |
| Country of Origin              | United States (US)               |
| Customs Tariff Number          | 0000000000                       |
| Global Commercial Alias        | 108710                           |
| Gross Weight                   | 0.404 kg                         |
| Invoice Description            | BX93 BELT                        |
| Made To Order                  | No                               |
| Material                       | Neoprene Rubber Body             |
| Minimum Order Quantity         | 1 piece                          |
| Order Multiple                 | 1 piece                          |
| Product Name                   | DODGE BELTS                      |

|                            |                                                          |
|----------------------------|----------------------------------------------------------|
| Product Net Height         | 5.08 cm                                                  |
| Product Net Length         | 13.66 cm                                                 |
| Product Net Weight         | 0.404 kg                                                 |
| Product Net Width          | 13.66 cm                                                 |
| Product Type               | Undefined                                                |
| Profile Type               | BX                                                       |
| Quote Only                 | No                                                       |
| Selling Unit of Measure    | piece                                                    |
| Standards                  | RMA                                                      |
| Stocked At<br>(Warehouses) | China<br>Alabama, United States<br>Alaska, United States |
| Temperature Range          | Maximum 140 °F<br>Minimum -30 °F                         |
| V-Belt Design              | Single                                                   |
| V-Belt Sides               | Single                                                   |
| WEEE B2C / B2B             | Business To Business                                     |
| WEEE Category              | Product Not in WEEE Scope                                |
| V-Belt Profiles            | Classical B                                              |
| Static Conductive          | Yes                                                      |
| Belt Height                | 0.40625 in                                               |
| Number of Bands            | 1                                                        |
| Oil Resistance             | Good                                                     |
| V-Belt Construction        | Cogged                                                   |

Categories

Mechanical Power Transmission → Belted Drives → V-Belts → Classical (A, B, C, D) → Single

