



PRODUCT-DETAILS

394385

R30 RIGID MALE FLG X 1/2 NK

General Information

Global Commercial Alias	394385
Product ID	7B394385
ABB Type Designation	R30 RIGID MALE FLG X 1/2 NK
Catalog Description	R30 RIGID MALE FLG X 1/2 NK

Additional Information

ABB Type Designation	R30 RIGID MALE FLG X 1/2 NK
Bore Diameter	Maximum 3.25 in Minimum 0.9375 in
Bore Length	3 in
Bushing Size	3030
Bushing Type	Taper-Lock
Country of Origin	United States (US)
Coupling Component	Flange
Coupling Size	R30
Coupling Style	Rigid
Coupling Type	Metallic
Customs Tariff Number	84833032
Flange Material	Cast Iron
Global Commercial Alias	394385
Gross Weight	20.43 kg
Horsepower Per 100 Rating	50.5 Hp
Invoice Description	R30 RIGID MALE FLG X 1/2 NK
Lubrication	None
Made To Order	No
Maximum Speed	2920 r/min
Minimum Order Quantity	1 piece
Number of Bolts	6
Order Multiple	1 piece
Outside Diameter	8.5 in
Product Name	DODGE COUPLINGS
Product Net Height	0 cm
Product Net Length	0 cm
Product Net Weight	20.43 kg
Product Net Width	0 cm
Product Type	Undefined

Quote Only	No
Rated Torque	31800 in-lb
Selling Unit of Measure	piece
Shaft Attachment	Bushed
Shaft Spacing	Close Coupled
Stocked At (Warehouses)	China Alabama, United States Alaska, United States
Temperature Rating	Maximum 285 °F Minimum -100 °F
Tightening Torque	Central Bolt 2000 in-lb
WEEE B2C / B2B	Business To Business
WEEE Category	Product Not in WEEE Scope

Categories

Mechanical Power Transmission → Couplings → Metallic Couplings → Rigid → Taper-Lock Rigid