

PRODUCT-DETAILS

## 2CSE1304EL

Miniature Circuit Breaker, 1P+N, C6 , breaking capacity 1,5kA



### General Information

|                     |                                                               |
|---------------------|---------------------------------------------------------------|
| Product ID          | 2CSE1304EL                                                    |
| EAN                 | 8012542752806                                                 |
| Catalog Description | Miniature Circuit Breaker, 1P+N, C6 , breaking capacity 1,5kA |
| Long Description    | Miniature Circuit Breaker, 1P+N, C6 , breaking capacity 1,5kA |

### Technical

|                                                     |                                                               |
|-----------------------------------------------------|---------------------------------------------------------------|
| Product Name                                        | Miniature Circuit Breaker, 1P+N, C6 , breaking capacity 1,5kA |
| Tripping Characteristic                             | C                                                             |
| Rated Operational Voltage                           | acc. to IEC 60947-2 230 V                                     |
| Rated Insulation Voltage (U <sub>i</sub> )          | 2000 V                                                        |
| Rated Impulse Withstand Voltage (U <sub>imp</sub> ) | 4 kV                                                          |
| Input Voltage Type                                  | AC                                                            |
| Rated Current (I <sub>n</sub> )                     | 6 A                                                           |
| Rated Short-Circuit Capacity (I <sub>cn</sub> )     | (230 V) 1.5 kA                                                |
| Rated Frequency (f)                                 | 50...60 Hz                                                    |
| Energy Limiting Class                               | 3                                                             |
| Number of Poles                                     | 2                                                             |
| Number of Protected Poles                           | 1                                                             |

|                       |                                                                   |
|-----------------------|-------------------------------------------------------------------|
| Overvoltage Category  | III                                                               |
| Accessories Available | Yes                                                               |
| Connecting Capacity   | Rigid 6 ... 6 mm <sup>2</sup><br>Flexible 6 ... 6 mm <sup>2</sup> |

## Environmental

|                         |                      |
|-------------------------|----------------------|
| Ambient Air Temperature | Operation -5...40 °C |
| Degree of Protection    | IP20                 |
| Pollution Degree        | 2                    |

## Dimensions

|                                     |          |
|-------------------------------------|----------|
| Width in Number of Modular Spacings | 2        |
| Product Net Width                   | 0.0275 m |
| Product Net Height                  | 0.0585 m |
| Product Net Depth / Length          | 0.0505 m |
| Product Net Weight                  | 0.006 kg |
| Built-In Depth (t <sub>2</sub> )    | 50 mm    |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | 12 piece      |
| Package Level 1 Width          | 0.07 m        |
| Package Level 1 Height         | 0.17 m        |
| Package Level 1 Depth / Length | 0.105 m       |
| Package Level 1 Gross Weight   | 0.75 kg       |
| Package Level 1 EAN            | 8012542752806 |

## Ordering

|                         |            |
|-------------------------|------------|
| Minimum Order Quantity  | 12 piece   |
| Customs Tariff Number   | 85365080   |
| Country of Origin       | Italy (IT) |
| Selling Unit of Measure | piece      |

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CSC100008U5101 |
| Instructions and Manuals       | 2CSC600290D0201 |

## Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 2CSC600290D0201 |
| Instructions and Manuals          | 2CSC600290D0201 |

| Classifications |                                                            |  |
|-----------------|------------------------------------------------------------|--|
| ETIM 6          | EC000042 - Miniature circuit breaker (MCB)                 |  |
| ETIM 7          | EC000042 - Miniature circuit breaker (MCB)                 |  |
| ETIM 8          | EC000042 - Miniature circuit breaker (MCB)                 |  |
| WEEE Category   | 5. Small Equipment (No External Dimension More Than 50 cm) |  |
| WEEE B2C / B2B  | Business To Consumer                                       |  |
| CN8             | 85365080                                                   |  |

**Categories**

Low Voltage Products and Systems → Switch Assortments → Flush Mounted Modular Range - ABB Sace → Design Elos → Flush Mounted Inserts with CoverPlate → Protection Devices

Low Voltage Products and Systems → Switch Assortments → Safety Devices → Protection Devices → Protection Devices - Flush Mounted → Protection Devices

