

PRODUCT-DETAILS

ESB63-40N-07

ESB63-40N-07 Installation Contactor



General Information

Extended Product Type	ESB63-40N-07
Product ID	1SAE351111M0740
Catalog Description	ESB63-40N-07 Installation Contactor
Long Description	The ESB63..N installation contactors are used to control single and three-phase loads up to 63 A and can be operated by AC or DC. These contactors are made for use in household applications as well as in industrial environments. The following benefits are provided: Hum-free operation, low power consumption and integrated overvoltage protection. Various contact combinations and accessories are available.

Ordering

Package Level 1 EAN	4013614521041
Minimum Order Quantity	4 piece
Customs Tariff Number	85365080

Popular Downloads

Instructions and Manuals	2CDC103043M6801
--------------------------	-----------------

Dimensions

Product Net Width	54 mm
Product Net Height	85 mm
Product Net Depth / Length	65 mm
Product Net Weight	0.4 kg

Technical

Rated Operational Voltage	Main Circuit 220 V DC Main Circuit 400 V AC
Rated Control Circuit Voltage (U _c)	400 V
Rated Frequency (f)	Control Circuit 400 Hz Control Circuit 50 Hz Control Circuit 60 Hz Control Circuit DC Main Circuit 50 Hz Main Circuit 60 Hz Main Circuit DC
Rated Operational Current AC-1 (I _e)	(NO) 63 A
Rated Operational Current AC-3 (I _e)	(230 V) Single Phase, NO 30 A (400 V) Three Phase, NO 30 A
Rated Operational Power AC-1 (P _e)	(230 V) Single Phase, NO 14.5 kW (400 V) Three Phase, NO 43.6 kW
Rated Operational Power AC-3 (P _e)	(230 V) Single Phase, NO 5 kW (400 V) Three Phase, NO 15 kW
Rated Operational Current AC-7a (I _e)	(NO) 63 A
Rated Operational Power AC-7a (P _e)	(230 V) Single Phase, NO 14.5 kW (400 V) Three Phase, NO 43.6 kW
Rated Operational Current AC-7b (I _e)	(230 V) Single Phase, NO 30 A (400 V) Three Phase, NO 30 A
Rated Operational Power AC-7b (P _e)	(230 V) Single Phase, NO 5 kW (400 V) Three Phase, NO 15 kW
Recommended Screw Driver	Control Circuit Pozidriv 1 Main Circuit Pozidriv 2
Rated Impulse Withstand Voltage (U _{imp})	6 kV
Rated Insulation Voltage (U _i)	500 V
Connecting Capacity Main Circuit	Flexible with Ferrule 1x 1.5 ... 16 mm ² Flexible with Ferrule 2x 1.5 ... 10 mm ² Flexible with Insulated Ferrule 1x 1.5 ... 16 mm ² Flexible with Insulated Ferrule 2x 1.5 ... 10 mm ² Flexible 2x 1.5 ... 10 mm ² Flexible 1x 1.5 ... 16 mm ² Rigid 1x 1.5 ... 25 mm ² Rigid 2x 1.5 ... 10 mm ²
Connecting Capacity Control Circuit	Flexible with Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Ferrule 2x 0.75 ... 1.0 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1 mm ² Flexible 1x 1 ... 4.0 mm ² Flexible 2x 1 ... 2.5 mm ² Rigid 1x 1 ... 4 mm ² Rigid 2x 1 ... 2.5 mm ²
Tightening Torque	Control Circuit 0.9 N·m Main Circuit 2.5 N·m
Wire Stripping Length	Control Circuit 7 mm Main Circuit 13 mm
Degree of Protection	IP20
Electrical Durability	AC-1 (NO) 100000 cycle AC-3 (NO) 240000 cycle AC-7a (NO) 100000 cycle

	AC-7b (NO) 240000 cycle
Mechanical Durability	1000000 cycle
Number of Poles	4
Number of Auxiliary Contacts NC	0
Number of Auxiliary Contacts NO	0
Number of Main Contacts NC	0
Number of Main Contacts NO	4
Width in Number of Modular Spacings	3
Pollution Degree	3
Standards	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 61095 UL 60947-1 UL 60947-4-1

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 480 V AC
Horsepower Rating UL/CSA	(220 ... 240 V AC) Single Phase, NO 5 Hp (220 ... 240 V AC) Three Phase, NO 10 Hp (440 ... 480 V AC) Single Phase, NO 7.5 Hp (440 ... 480 V AC) Three Phase, NO 15 Hp
Connecting Capacity Main Circuit UL/CSA	Solid 16-4 AWG Stranded 16-4 AWG
Connecting Capacity Control Circuit UL/CSA	Solid 16-10 AWG Stranded 16-10 AWG
Tightening Torque UL/CSA	Control Circuit 8 in-lb Main Circuit 20 in-lb

Environmental

Ambient Air Temperature	Operation -25 ... +55 °C Storage -40 ... +80 °C
Maximum Operating Altitude Permissible	2000 m
Resistance to Shock acc. to IEC 60068-2-27	11 ms Pulse 15g
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

ABS Certificate	1SAA920000-0101
CB Certificate	1SAA920005-2001
CQC Certificate	CQC2017010304993562 CQC2017010304993563
cULus Certificate	cUL_E191658
Declaration of Conformity - CCC	2020980304001310 2020980304001313
Declaration of Conformity - CE	1SAD938506-0302
Declaration of Conformity - UKCA	1SAD938501-1302
DNV Certificate	1SAA920000-0306
EAC Certificate	1SAA920001-2702
Environmental Information	1SAC200065H0009

Instructions and Manuals	2CDC103043M6801
NF Certificate	1SAA920001-1202
RINA Certificate	1SAA920000-0801
RMRS Certificate	1SAA920000-0705
RoHS Information	1SAD938506-0302

nf

Container Information