

PRODUCT-DETAILS

DRAF09-11S 24-60V50/60HZ

DRAF09-11S 24-60V50/60HZ Enclosure



General Information

Extended Product Type	DRAF09-11S 24-60V50/60HZ
Product ID	1SBK134237R1100
EAN	3471522144218
Catalog Description	DRAF09-11S 24-60V50/60HZ Enclosure
Long Description	DRAF09-11S 24-60V50/60HZ enclosed Direct-On-Line starter with AF contactors

Technical

Product Name	Enclosure
Number of Main Contacts NC	0
Number of Main Contacts NO	3
Number of Auxiliary Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Commands	2
Housing Material	ABS
Housing Color	White

Environmental

Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP66
----------------------	---

RoHS Status

Following EU Directive 2011/65/EU

Dimensions

Product Net Width	107 mm
Product Net Height	230 mm
Product Net Depth / Length	131 mm
Product Net Weight	0.82 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	243 mm
Package Level 1 Height	143 mm
Package Level 1 Depth / Length	112 mm
Package Level 1 Gross Weight	0.82 kg
Package Level 1 EAN	3471522144218

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900
Country of Origin	Bulgaria (BG)
Selling Unit of Measure	piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SBD250009U1000
Instructions and Manuals	1SBC101048M6801
RoHS Information	1SBD250009U1000
UL Certificate	UL_20150729-E312527-16-1
UL Listing Card	UL_E312527

Popular Downloads

Data Sheet, Technical Information	1SBC100199C0201
Instructions and Manuals	1SBC101048M6801
UL Listing Card	UL_E312527

Classifications

ETIM 6	EC000200 - Enclosure for control circuit devices
ETIM 7	EC000200 - Enclosure for control circuit devices
ETIM 8	EC000200 - Enclosure for control circuit devices
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	8536 49 00
eClass	V11.0 : 27371205

Categories

Low Voltage Products and Systems → Control Products → Contactor Starters → Enclosed Starters

