


PRODUCT-DETAILS

CP430C-ETH

CP430 C-ETH Control Panel 5.7" STN Touch



General Information

Extended Product Type	CP430C-ETH
Product ID	1SBP260186R1001
ABB Type Designation	CP430C-ETH
EAN	3471522601865
Catalog Description	CP430 C-ETH Control Panel 5.7" STN Touch
Long Description	CP430 C-ETH Control Panel 1 menu 5 defined keys 5.7" STN Touch screen 256 Colors + Ethernet

Additional Information

ABB Type Designation	CP430C-ETH
Ambient Air Temperature	Operation 0 ... +50 °C Storage -10 ... +60 °C
Battery Type	Portable
CN8	84716070
Communication	Depend on Driver
Communication Interface	Ethernet
Communication Speed	4.8 ... 187.5 kBd
Country of Origin	Germany (DE) France (FR)
Customs Tariff Number	84716070

Data Sheet, Technical Information	1SBC159107L0201
Declaration of Conformity - CE	1SBD240576C1000
Display Type	STN Touch + keys
EAN	3471522601865
Environmental Information	1SBD240186E1000
Fieldbus Interface Type	Modbus RTUAC500_ModbusASCIIothers (contact us)
Fuse Size	5 x 20_MMTx
Fuse Type	BEL.5TT 1.6-R
GSD-file for PROFIBUS Communication	No
Gross Weight	1.34 kg
Instructions and Manuals	1SBC159103M0201
Instructions and Manuals (Part 2)	1SBC159106M0202
Invoice Description	CP430 C-ETH Control Panel 5.7" STN Touch
Made To Order	No
Memory Size User Data	512 kB
Memory Size User Program	4000 kB
Memory Type User Data	512 kilobyte RAM
Memory Type User Program	4 MB ROM
Minimum Order Quantity	1 piece
Mounting Position	0 to 135 °
Mounting Type	Front face
Mounting on DIN Rail	No
Number of Characters Per Line	40
Number of Display Lines	30
Number of Function Keys	5
Number of LEDs	0
Operating Mode	off-lineon-line
Order Multiple	1 piece
	20 V·A
Power Supply	24 V DC
Product Main Type	CP430
Product Name	Control Panel
Product Net Height	145 mm
Product Net Length	60 mm
Product Net Weight	0.81 kg
Product Net Width	195 mm
Product Type	PLC-CP400
Profibus	No
Programming Software	CP400 Soft
Quote Only	No
Real-time Clock	Yes
Release Type	V10.10.10
RoHS Date	237

RoHS Information	1SBD340002R0202
Screen Color	256 colors
Screen Resolution	240 pixel
Screen Size	5.7 in
Security	password protection with 9 user levels
Selling Unit of Measure	piece
Serial Port 1 Type	RS232RS485
Serial Port 2 Type	RS232RS422RS485
Service Life	75000 hour
Short Description	CP430 C-ETH Control Panel 5.7" STN Touch screen
Short-Circuit Protective Devices	gG Type Fuses Integrated
Software Function	alarm managementrecipe managementtrendsmacro & laddersub-screen
Stocked At (Warehouses)	Menden, Germany Menden, Germany New Berlin,Wisconsin, United States Singapore, Singapore Beijing, China Singapore, Singapore Australia, Australia
Supply Voltage	20.4 ... 27.6 V DC
USB Port 1 Type	no
USB Port 2 Type	no
Viewing Area Height	88.4 mm
Viewing Area Length	117.2 mm
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

PLC Automation → Legacy products → CP400 → Devices

