

PRODUCT-DETAILS

CP415M

CP415M Control Panel



General Information

Extended Product Type	CP415M
Product ID	1SBP260191R1001
ABB Type Designation	CP415M
EAN	3471522601919
Catalog Description	CP415M Control Panel
Long Description	CP415 M Control Panel 3.5" STN Touch screen 16 grey levels

Additional Information

ABB Type Designation	CP415M
Ambient Air Temperature	Operation 0 ... +50 °C Storage -10 ... +60 °C
Battery Type	Portable
CN8	85371091
Communication	Depend on Driver
Communication Interface	no
Communication Speed	4.8 ... 187.5 kBd
Country of Origin	Taiwan, Province Of China (TW)
Customs Tariff Number	85371091
Data Sheet, Technical Information	1SBC159107L0202
Declaration of Conformity - CE	1SBD240514C1000

Display Type	STN Touch
EAN	3471522601919
Environmental Information	1SBD240191E1000
Fieldbus Interface Type	Modbus RTUAC500_ModbusASCIlothers (contact us)
Fuse Size	5 x 20_MMTx
Fuse Type	BEL.5TT 1-R
Gross Weight	2 kg
Instructions and Manuals	1SBC159107M0201
Instructions and Manuals (Part 2)	1SBC159106M0202
Invoice Description	CP415M Control Panel
Made To Order	No
Memory Size User Program	4000 kB
Memory Type User Program	4 MB ROM
Minimum Order Quantity	1 piece
Mounting Position	0 to 135 °
Mounting Type	Front face
Mounting on DIN Rail	No
Number of Characters Per Line	40
Number of Display Lines	30
Number of Function Keys	5
Number of LEDs	0
Operating Mode	off-lineon-line
Order Multiple	1 piece
	20 V·A
Power Supply	24 V DC
Product Main Type	CP415
Product Name	Control Panel
Product Net Height	96 mm
Product Net Length	41 mm
Product Net Weight	0.21 kg
Product Net Width	96 mm
Product Type	PLC-CP400
Profibus	No
Programming Software	CP400 Soft
Quote Only	No
Real-time Clock	Yes
Release Type	V11.12.10
RoHS Information	1SBD340002R0202
Screen Color	16 grey levels
Screen Resolution	240 x 240 pixel
Screen Size	1:1 screen 3.5 in
Screen Type	FSTN grey, LED backlight, touch screen
Security	password protection with 9 user levels
Selling Unit of Measure	piece
Serial Port 1 Type	RS232/RS422/RS485
Service Life	30000 hour
Short Description	CP415 M Control Panel 3.5" STN Touch screen 16
Short-Circuit Protective Devices	gG Type Fuses Integrated
Software Function	alarm managementtrendsmacro & laddersub-screen

Stocked At (Warehouses)	Menden, Germany
Supply Voltage	20.4 ... 27.6 V DC
UL Certificate	NRAQ.E240320
UNSPSC	32151703
Viewing Area Height	58.5 mm
Viewing Area Length	58.5 mm
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
cUL Certificate	1SAA960000-1709
eClass	27-33-02-01

Categories

PLC Automation → Legacy products → CP400 → Devices

