


PRODUCT-DETAILS

CP430T

CP430 T-ETH Control Panel 5.7" TFT Touch



General Information

Extended Product Type	CP430T
Product ID	1SBP260195R1001
ABB Type Designation	CP430T
EAN	3471522601957
Catalog Description	CP430 T-ETH Control Panel 5.7" TFT Touch
Long Description	CP430 T Control Panel 1 menu 5 defined keys 5.7" TFT Touch screen 64K Colors

Additional Information

ABB Type Designation	CP430T
Ambient Air Temperature	Operation 0 ... +50 °C Storage -10 ... +60 °C
Battery Type	Portable
CN8	85381000
Communication	Depend on Driver
Communication Interface	no
Communication Speed	4.8 ... 187.5 kBd
Country of Origin	Taiwan, Province Of China (TW)
Customs Tariff Number	85381000
Data Sheet, Technical	1SBC159107L0202

Information

Declaration of Conformity - CE	1SBD240515C1000
Display Type	TFT Touch + keys
EAN	3471522601957
Fieldbus Interface Type	Modbus RTUAC500_ModbusASCIIothers (contact us)
Fuse Size	5 x 20_MMTx
Fuse Type	SLEEK.36ESr
Gross Weight	1.31 kg
Instructions and Manuals	1SBC159103M0202
Instructions and Manuals (Part 2)	1SBC159106M0202
Invoice Description	CP430 T-ETH Control Panel 5.7" TFT Touch
Made To Order	No
Memory Size User Data	512 kB
Memory Size User Program	4000 kB
Memory Type User Data	512 kilobyte RAM
Memory Type User Program	4 MB ROM
Minimum Order Quantity	1 piece
Mounting Position	0 to 135 °
Mounting Type	Front face
Mounting on DIN Rail	No
Number of Characters Per Line	40
Number of Display Lines	30
Number of Function Keys	5
Number of LEDs	0
Operating Mode	off-lineon-line
Order Multiple	1 piece
Package Level 1 Units	0 carton
Part Type	New
	20 V·A
Power Supply	24 V DC
Product Main Type	CP430
Product Name	"Color TFT-Touchscreen 5,7","USB
Product Net Height	145 mm
Product Net Length	60 mm
Product Net Weight	0.86 kg
Product Net Width	195 mm
Product Type	PLC-CP400
Profibus	No
Programming Software	CP400 Soft
Quote Only	No
Real-time Clock	Yes
Release Type	V11.11.10
RoHS Information	1SBD340002R0202
Screen Color	64k colors

Screen Resolution	320 x 240 pixel
Screen Size	4:3 screen 5.7 in
Screen Type	TFT color, CCFL backlight, touch screen
Security	password protection with 9 user levels
Selling Unit of Measure	piece
Serial Port 1 Type	RS232/RS485
Serial Port 2 Type	RS232/RS422/RS485
Service Life	60000 hour
Short Description	CP430 T Control Panel 5.7" TFT Touch screen 64KC
Short-Circuit Protective Devices	gG Type Fuses Integrated
Software Function	alarm managementrecipe managementtrendsmacro & laddersub-screen
Stocked At (Warehouses)	Menden, Germany Singapore, Singapore
Supply Voltage	20.4 ... 27.6 V DC
UL Certificate	NRAQ.E240320
USB Port 1 Type	Host, version 2.0
USB Port 2 Type	1 Device Ver. 2.0
Viewing Area Height	88.4 mm
Viewing Area Length	117.2 mm
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
cUL Certificate	1SAA960000-1709

Categories

PLC Automation → Legacy products → CP400 → Devices

