

PRODUCT-DETAILS

07CR41-SPRING

07CT41:AC31,PLC 8DI/6DO-Trans., 34kB, 24



General Information

Extended Product Type	07CR41-SPRING
Product ID	1SBP260520R1001
ABB Type Designation	07CR41
Catalog Description	07CT41:AC31,PLC 8DI/6DO-Trans., 34kB, 24
Long Description	07CR41:AC31,PLC 8DI/6DO-Rel., 34kB,24VDC, Spring

Additional Information

ABB Type Designation	07CR41
Ambient Air Temperature	Operation 0 ... +55 °C Storage -40 ... +75 °C
Battery Type	Portable
CN8	85371091
Country of Origin	France (FR)
Customs Tariff Number	85389099
DNV Certificate	DNV_A-8389
Data Sheet, Technical Information	1SBC260400R1001
Declaration of Conformity - CE	1SBD240550C1000
Environmental Information	1SBD240020E1000
GL Certificate	GL_17 179-00 HH
Gross Weight	0.35 kg
Instructions and	1SBC260400R1001

Manuals

Invoice Description	07CT41:AC31,PLC 8DI/6DO-Trans., 34kB, 24
LR Certificate	LR_00-20009-E1
Made To Order	No
Maximum Hardware Counter Input Frequency	7 kHz
Maximum Number of Analog I/Os	48 AI
Maximum Number of Digital I/Os	110
Maximum Operating Altitude Permissible	2000 m
Memory Size	34 kB
Memory Size User Data	4.4 kB
Memory Size User Program	34 kB
Memory Type User Data	non-volatile RAM
Memory Type User Program	Flash EPROM
Minimum Order Quantity	1 piece
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Number of Digital Inputs DC 24V	8
Number of Digital Output Relays	6
Number of Hardware Counters	2
Order Multiple	1 piece
Output Current	2 A
Output Voltage (U _{out})	24 V DC
Parallel Extension	1
Primary Voltage	24 V DC
Product Depth	84 mm
Product Main Type	07CR41
Product Name	Distributed Automation PLCs
Product Net Height	93 mm
Product Net Length	85 mm
Product Net Weight	0.35 kg
Product Net Width	120 mm
Product Type	PLC-AC31-40/50
Programming Software	AC31GRAPH, 907AC1131
Quote Only	No
Real-time Clock	Yes
Selling Unit of Measure	piece
Serial Port 1 Type	PR,MODBUS
Short Description	07CR41:AC31,PLC 8DI/6DO-Rel., 34kB.24VDC, Spring
Speed for 1000 instructions (65% Logic, 35% Word)	1.2 ms
Stocked At (Warehouses)	Menden, Germany
Supply Voltage	DC 24 V
UL Certificate	UL_E134045 Vol3 Sec2
UNSPSC	32151705
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	27-24-22-07

Categories

PLC Automation → Legacy products → AC31 and previous series → AC31 PLCs and previous series

