

PRODUCT-DETAILS

DP40C2P-2/S

DP40C2P-2/S contactor



General Information

Extended Product Type	DP40C2P-2/S
Product ID	1SBX104202R1300
EAN	0804325565615
Catalog Description	DP40C2P-2/S contactor
Long Description	DP40C2P-2/S DP contactor provide outstanding performance in various HVAC application and meet all relevant standards, including UL, CSA and IEC. Industry standard mounting plate provides easily accessible mounting holes.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

Dimensions

Product Net Width	52.7 mm
Product Net Depth / Length	60.1 mm
Product Net Height	82.9 mm
Product Net Weight	0.27 kg

Technical

Number of Main Contacts NO	2
Standards	UL 508 IEC 60947-4-1
Rated Frequency (f)	Control Circuit 50 Hz Control Circuit 60 Hz
Rated Control Supply Voltage (U _s)	208 / 240 V AC

Environmental

Ambient Air Temperature	Operation -40 ... +65 °C
RoHS Status	No declaration needed

Technical UL/CSA

Horsepower Rating UL/CSA	(110 ... 120 V AC) Single Phase 2 Hp (220 ... 240 V AC) Single Phase 3 Hp
Full Load Amps AC Resistance (Heating)	(600 V AC) 50 A
Full Load Amps Motor Use	40 A
Locked Rotor Amps	(480 V AC) 160 A (600 V AC) 120 A

Certificates and Declarations (Document Number)

cUL Certificate	cUL_E224401
Declaration of Conformity - CE	NoDecNee
RoHS Information	NoDecNee
UL Certificate	UL_E224401

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	50.8 mm
Package Level 1 Depth / Length	63.5 mm
Package Level 1 Height	88.9 mm

Classifications

Object Classification Code	Q
ETIM 7	EC000066 - Power contactor, AC switching
UNSPSC	39121529

Categories

Low Voltage Products and Systems → Control Products → Contactors → Definite Purpose Contactors

