

PRODUCT-DETAILS

DP60C3P-4

DP60C3P-4 Contactor



General Information

Extended Product Type	DP60C3P-4
Product ID	1SBX106300R1500
EAN	0662019755700
Catalog Description	DP60C3P-4 Contactor
Long Description	DP60C3P-4 DP contactor provide outstanding performance in various HVAC application and meet all relevant standards, including UL, CSA and IEC. Industry standard mounting plate provides easily accessible mounting holes.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

Dimensions

Product Net Width	70 mm
Product Net Depth / Length	83.7 mm
Product Net Height	95.8 mm
Product Net Weight	0.64 kg

Technical

Number of Main Contacts NO	3
Standards	IEC 60947-4-1 UL 508
Rated Frequency (f)	Control Circuit 50 Hz Control Circuit 60 Hz
Rated Control Supply Voltage (U _s)	480 V AC

Environmental

RoHS Status	No declaration needed
-------------	-----------------------

Technical UL/CSA

Horsepower Rating UL/CSA	(110 ... 120 V AC) Single Phase 5 Hp (208 V AC) Three Phase 20 Hp (220 ... 240 V AC) Single Phase 10 Hp (220 ... 240 V AC) Three Phase 25 Hp (440 ... 480 V AC) Three Phase 30 Hp (550 ... 600 V AC) Three Phase 30 Hp
Full Load Amps AC Resistance (Heating)	(600 V AC) 75 A
Full Load Amps Motor Use	60 A
Locked Rotor Amps	(480 V AC) 300 A (600 V AC) 240 A

Certificates and Declarations (Document Number)

cUL Certificate	cUL_E224401
Declaration of Conformity - CE	NoDecNee
RoHS Information	NoDecNee
UL Certificate	UL_E224401

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	76.2 mm
Package Level 1 Depth / Length	88.9 mm
Package Level 1 Height	101.6 mm

Classifications

Object Classification Code	Q
ETIM 7	EC000066 - Power contactor, AC switching
UNSPSC	39121529

Categories

Low Voltage Products and Systems → Control Products → Contactors → Definite Purpose Contactors

