

## PRODUCT-DETAILS

# DP60C3P-1/S

## DP60C3P-1/S contactor



### General Information

|                       |                                                                                                                                                                                                                              |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | DP60C3P-1/S                                                                                                                                                                                                                  |
| Product ID            | 1SBX106306R1200                                                                                                                                                                                                              |
| EAN                   | 0804325314466                                                                                                                                                                                                                |
| Catalog Description   | DP60C3P-1/S contactor                                                                                                                                                                                                        |
| Long Description      | DP60C3P-1/S DP contactor provide outstanding performance in various HVAC application and meet all relevant standards, including UL, CSA and IEC. Industry standard mounting plate provides easily accessible mounting holes. |

### Ordering

|                        |          |
|------------------------|----------|
| Minimum Order Quantity | 1 piece  |
| Customs Tariff Number  | 85365080 |

### Dimensions

|                            |         |
|----------------------------|---------|
| Product Net Width          | 70 mm   |
| Product Net Depth / Length | 95.8 mm |
| Product Net Height         | 99.2 mm |
| Product Net Weight         | 0.64 kg |

### Technical

|                                                   |                                                |
|---------------------------------------------------|------------------------------------------------|
| Number of Main<br>Contacts NO                     | 3                                              |
| Standards                                         | UL 508<br>IEC 60947-4-1                        |
| Rated Frequency (f)                               | Control Circuit 50 Hz<br>Control Circuit 60 Hz |
| Rated Control Supply<br>Voltage (U <sub>s</sub> ) | 120 V AC                                       |

## Environmental

|             |                       |
|-------------|-----------------------|
| RoHS Status | No declaration needed |
|-------------|-----------------------|

## Technical UL/CSA

|                                           |                                                                                                                                                                                                                                       |
|-------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Horsepower Rating<br>UL/CSA               | (110 ... 120 V AC) Single Phase 5 Hp<br>(208 V AC) Three Phase 20 Hp<br>(220 ... 240 V AC) Single Phase 10 Hp<br>(220 ... 240 V AC) Three Phase 25 Hp<br>(440 ... 480 V AC) Three Phase 30 Hp<br>(550 ... 600 V AC) Three Phase 30 Hp |
| Full Load Amps AC<br>Resistance (Heating) | (600 V AC) 75 A                                                                                                                                                                                                                       |
| Full Load Amps Motor<br>Use               | 60 A                                                                                                                                                                                                                                  |
| Locked Rotor Amps                         | (480 V AC) 300 A<br>(600 V AC) 240 A                                                                                                                                                                                                  |

## Certificates and Declarations (Document Number)

|                                   |             |
|-----------------------------------|-------------|
| cUL Certificate                   | cUL_E224401 |
| Declaration of<br>Conformity - CE | NoDecNee    |
| RoHS Information                  | NoDecNee    |
| UL Certificate                    | UL_E224401  |

## Container Information

|                                   |          |
|-----------------------------------|----------|
| Package Level 1 Units             | 1 piece  |
| Package Level 1 Width             | 76.2 mm  |
| Package Level 1 Depth /<br>Length | 88.9 mm  |
| Package Level 1 Height            | 101.6 mm |

## Classifications

|                               |                                          |
|-------------------------------|------------------------------------------|
| Object Classification<br>Code | Q                                        |
| ETIM 7                        | EC000066 - Power contactor, AC switching |
| UNSPSC                        | 39121529                                 |

---

## Categories

---

Low Voltage Products and Systems → Control Products → Contactors → Definite Purpose Contactors

