

## PRODUCT-DETAILS

# EOT32U3P4-2P

## EOT32U3P4-2P Enclosed Disconnect Switch



### General Information

|                       |                                                                                                                                                                                                                                      |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | EOT32U3P4-2P                                                                                                                                                                                                                         |
| Product ID            | 1SCA022861R7350                                                                                                                                                                                                                      |
| EAN                   | 6417019310053                                                                                                                                                                                                                        |
| Catalog Description   | EOT32U3P4-2P Enclosed Disconnect Switch                                                                                                                                                                                              |
| Long Description      | Enclosed Switch Disconnecter, 3-p. Max. Horse power rating at three phase 480V 20HP.<br>General purpose current rating 40A. Plastic enclosure, NEMA Type 4/4X Watertight, Pistol handle. Interlocked cover. Defeatable interlocking. |

### Ordering

|                        |             |
|------------------------|-------------|
| Minimum Order Quantity | 1 piece     |
| Customs Tariff Number  | 85363030    |
| Country of Origin      | Mexico (MX) |

### Popular Downloads

|                                   |                    |
|-----------------------------------|--------------------|
| Data Sheet, Technical Information | 1SCC340016C0201    |
| Instructions and Manuals          | 1SCC340019M0202    |
| Mechanical Drawings               | EOTK4161081P12.igs |

## Dimensions

|                               |                     |
|-------------------------------|---------------------|
| Product Net Width             | 100 mm<br>3.94 in   |
| Product Net Height            | 161.4 mm<br>6.35 in |
| Product Net Depth /<br>Length | 81 mm<br>3.19 in    |
| Product Net Weight            | 0.62 kg<br>1.37 lb  |

## Technical

|                                                                   |                                                                                                   |
|-------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|
| Rated Operational Current<br>AC-22A ( $I_e$ )                     | (380 ... 415 V) 40 A<br>(690 V) 40 A                                                              |
| Rated Operational Current<br>AC-23A ( $I_e$ )                     | (690 V) 23 A<br>(690 V) 380415V12 A                                                               |
| Conventional Thermal<br>Current ( $I_{the}$ )                     | 40 A                                                                                              |
| Rated Insulation Voltage<br>( $U_i$ )                             | acc. to IEC/EN 60664-1 750 V                                                                      |
| Rated Operational Voltage                                         | Main Circuit 750 V                                                                                |
| Rated Short-Circuit<br>Making Capacity ( $I_{cm}$ )               | (690 V AC) 0.71 kA                                                                                |
| Rated Short-time<br>Withstand Current Low<br>Voltage ( $I_{cw}$ ) | for 1 s 0.5 kA                                                                                    |
| Pollution Degree                                                  | 3                                                                                                 |
| Handle Color                                                      | Black                                                                                             |
| Handle Type                                                       | Pistol handle                                                                                     |
| Position of Line Terminals                                        | Top In - Bottom Out                                                                               |
| Standards                                                         | IEC 60947-1, -3 / UL 508                                                                          |
| Number of Poles                                                   | 3                                                                                                 |
| Connecting Capacity Main<br>Circuit                               | Screw Clamp 0.75...10 mm <sup>2</sup><br>Screw Clamp / PE Terminal 1pcs, 0.5...16 mm <sup>2</sup> |
| Cable Entry Position                                              | Up/Down                                                                                           |
| Cable Outlets Per Side                                            | 2x(ø0.5 / 12.7+ø0.75 / 19.1)                                                                      |
| Degree of Protection                                              | acc. to IEC 60529 IP65                                                                            |
| Enclosure Type                                                    | NEMA Type 4/4X Watertight                                                                         |
| Enclosure Material                                                | Plastic                                                                                           |
| Mounted Auxiliary<br>Contacts                                     | 1 NO, 1 NC                                                                                        |
| Terminal Type                                                     | Screw Terminals                                                                                   |
| Tightening Torque                                                 | acc. IEC 60947-1 0.8 N·m                                                                          |
| Mechanical Durability                                             | 20000                                                                                             |

## Technical UL/CSA

|                                     |                                      |
|-------------------------------------|--------------------------------------|
| Maximum Operating<br>Voltage UL/CSA | 600 V                                |
| Horsepower Rating                   | (220 ... 240 V AC) Three Phase 10 Hp |

|                             |                                      |
|-----------------------------|--------------------------------------|
| UL/CSA                      | (480 V AC) 20 Hp<br>(600 V AC) 25 Hp |
| Ampere Rating UL/CSA        | 40 A                                 |
| Tightening Torque<br>UL/CSA | Main Circuit 7 in-lb                 |

Certificates and Declarations (Document Number)

|                                   |                 |
|-----------------------------------|-----------------|
| Declaration of Conformity<br>- CE | 1CC340035D2701  |
| Instructions and Manuals          | 1SCC340019M0202 |

Container Information

|                                   |                    |
|-----------------------------------|--------------------|
| Package Level 1 Units             | 1 piece            |
| Package Level 1 Width             | 135 mm             |
| Package Level 1 Depth /<br>Length | 172 mm             |
| Package Level 1 Height            | 112 mm             |
| Package Level 1 Gross<br>Weight   | 0.62 kg<br>1.37 lb |
| Package Level 1 EAN               | 6417019310053      |

Classifications

|                            |                                                            |
|----------------------------|------------------------------------------------------------|
| Object Classification Code | Q                                                          |
| ETIM 5                     | EC000216 - Switch disconnect                               |
| ETIM 6                     | EC000216 - Switch disconnect                               |
| ETIM 7                     | EC000216 - Switch disconnect                               |
| ETIM 8                     | EC000216 - Switch disconnect                               |
| UNSPSC                     | 39122233                                                   |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Enclosed Switches → Enclosed Disconnect Switches

