


PRODUCT-DETAILS

OT250E12CFP

OT250E12CFP CHANGE-OVER SWITCH



General Information

Extended Product Type	OT250E12CFP
Product ID	1SCA108609R1001
EAN	6417019399959
Catalog Description	OT250E12CFP CHANGE-OVER SWITCH
Long Description	OT250E12CFP CHANGE-OVER SWITCH, Handle and shaft included, Fast transition

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC303008M0203

Dimensions

Product Net Width	170 mm
Product Net Height	150 mm

Product Net Depth / Length	160 mm
Product Net Weight	3.245 kg 7.15 lb

Technical

Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Current AC-31B (I_e)	(380 ... 415 V) 250 A
Rated Operational Current AC-33B (I_e)	(380 ... 415 V) 250 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 140 kW (500 V) 170 kW (690 V) 250 kW
Conventional Free-air Thermal Current (I_{th})	$q = 40\text{ °C}$ 250 A
Conventional Thermal Current (I_{the})	Fully Enclosed 250 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 8 kiloampere rms
Power Loss	6.5 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Switches Operating Mechanism	Mechanism Between the Poles 12 (Between the Poles)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	3
Degree of Protection	Front IP20
Transition Type	Fast

Environmental

Environmental Information	1SCC303050D0201
---------------------------	-----------------

Certificates and Declarations (Document Number)

Declaration of	1SCC303003D0202
----------------	-----------------

Conformity - CE

Environmental Information	1SCC303050D0201
Instructions and Manuals	1SCC303008M0203
RoHS Information	1SCC301149D0202

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	186 mm 7.32 in
Package Level 1 Depth / Length	300 mm 11.81 in
Package Level 1 Height	185 mm 7.28 in
Package Level 1 Gross Weight	3.515 kg 7.75 lb
Package Level 1 EAN	6417019399959

Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3641671

Categories

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Manual Change-over Switches

