


PRODUCT-DETAILS

OT1600E22-135

OT1600E22-135 DISCONNECTOR



General Information

Extended Product Type	OT1600E22-135
Product ID	1SCA159247R1001
EAN	6417019886947
Catalog Description	OT1600E22-135 DISCONNECTOR
Long Description	Base mounting 4-pole, front operated disconnecter up to 1500Vdc, Utilization category DC-20B, handle and shaft not included, lug terminal , bolt kit included

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Instructions and Manuals	1SCC301100M0201
--------------------------	-----------------

Dimensions

Product Net Width	414.5 mm
-------------------	----------

Product Net Height	372 mm
Product Net Depth / Length	148.5 mm
Product Net Weight	21.6 kg

Technical

Conventional Thermal Current (I_{the})	Fully Enclosed 1600 A
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 1500 V
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 0.3 s 65 kA
Power Loss	at Rated Operating Conditions per Pole 48 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Standards	IEC 60947-3
Mounting Type	Base mounting
Number of Poles	4
Degree of Protection	Front IP00
Terminal Type	Lug terminals
Tightening Torque	acc. IEC 60947-1 50 ... 75 N·m
Mechanical Durability	6000
Lock Type	No

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC301229D2701
Instructions and Manuals	1SCC301100M0201
RoHS Information	1SCC301149D0203

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	400 mm
Package Level 1 Depth / Length	435 mm
Package Level 1 Height	170 mm
Package Level 1 EAN	6417019886947

Classifications

Object Classification Code	Q
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

