


## PRODUCT-DETAILS

# XLP00-A40/95-B-3BC-below

## XLP00-A40/95-B-3BC-below Fuse Switch Disconnecter



### General Information

|                       |                                                                          |
|-----------------------|--------------------------------------------------------------------------|
| Extended Product Type | XLP00-A40/95-B-3BC-below                                                 |
| Product ID            | 1SEP101889R0002                                                          |
| EAN                   | 7025840016380                                                            |
| Catalog Description   | XLP00-A40/95-B-3BC-below Fuse Switch Disconnecter                        |
| Long Description      | XLP00,3-pole,160A, incl. A40/95 adapter and 3 Bridge Clamps, cable below |

### Ordering

|                        |               |
|------------------------|---------------|
| Minimum Order Quantity | 1 piece       |
| Customs Tariff Number  | 85389099      |
| Country of Origin      | Bulgaria (BG) |

### Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SEC312012D0201 |
|-----------------------------------|-----------------|

### Dimensions

|                            |        |
|----------------------------|--------|
| Product Net Width          | 105 mm |
| Product Net Height         | 187 mm |
| Product Net Depth / Length | 175 mm |

|                    |        |
|--------------------|--------|
| Product Net Weight | 1.1 kg |
|--------------------|--------|

## Technical

|                                                            |                                  |
|------------------------------------------------------------|----------------------------------|
| Rated Operational Current AC-21B (I <sub>e</sub> )         | (690 V) 125 A                    |
| Rated Operational Current AC-22B (I <sub>e</sub> )         | (500 V) 160 A                    |
| Rated Operational Current AC-23B (I <sub>e</sub> )         | (400V) 125 A                     |
| Rated Impulse Withstand Voltage (U <sub>imp</sub> )        | Main Circuit 8 kV                |
| Rated Operational Voltage                                  | 400 V AC<br>500 V AC<br>690 V AC |
| Rated Frequency (f)                                        | Main Circuit 50/60 Hz            |
| Rated Conditional Short-Circuit Current (I <sub>nc</sub> ) | (690 V) 50 kiloampere rms        |
| Handle Type                                                | Front cover 3P                   |
| Fuse Size                                                  | NH00<br>NH000                    |
| Fuse System                                                | DIN                              |
| Standards                                                  | IEC60947-3                       |
| Special Functions                                          | Not Included                     |
| Mounting Type                                              | 40mm Busbar System               |
| Number of Poles                                            | 3                                |
| Degree of Protection                                       | IP30                             |
| Terminal Type                                              | Cable Clamp                      |
| Device Type Manager (DTM)                                  | Fuseswitchdisconnector           |
| Fuse Type                                                  | NH                               |
| Electronic Fuse Monitoring                                 | No                               |

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 1SEP500050P0001 |
|--------------------------------|-----------------|

## Container Information

|                                |                     |
|--------------------------------|---------------------|
| Package Level 1 Units          | shrink-wrap 1 piece |
| Package Level 1 Width          | 105 mm              |
| Package Level 1 Depth / Length | 175 mm              |
| Package Level 1 Height         | 187 mm              |
| Package Level 1 Gross Weight   | 1.1 kg              |
| Package Level 1 EAN            | 7025840016380       |
| Package Level 2 EAN            | 7025840016380       |

## Classifications

|                            |                                     |
|----------------------------|-------------------------------------|
| Object Classification Code | S                                   |
| ETIM 4                     | EC001040 - Fuse switch disconnector |
| ETIM 5                     | EC001040 - Fuse switch disconnector |

|               |                                                            |
|---------------|------------------------------------------------------------|
| ETIM 6        | EC001040 - Fuse switch disconnecter                        |
| ETIM 7        | EC001040 - Fuse switch disconnecter                        |
| ETIM 8        | EC001040 - Fuse switch disconnecter                        |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

---

## Categories

---

Low Voltage Products and Systems → Fusegear → Fuse Switch Disconnectors → EasyLine

