

## PRODUCT-DETAILS

# XRG00-50/10-4P-MOT

## XRG00-50/10-4P-MOT Switch disconnecter fuse



### General Information

|                       |                                                                                                        |
|-----------------------|--------------------------------------------------------------------------------------------------------|
| Extended Product Type | XRG00-50/10-4P-MOT                                                                                     |
| Product ID            | 1SEP204480R7702                                                                                        |
| EAN                   | 3800161650291                                                                                          |
| Catalog Description   | XRG00-50/10-4P-MOT Switch disconnecter fuse                                                            |
| Long Description      | Four pole Switch Disconnecter Fuse for 50mm busbar distance and 10mm busbar thickness, including motor |

### Ordering

|                       |               |
|-----------------------|---------------|
| Customs Tariff Number | 85363000      |
| Country of Origin     | Bulgaria (BG) |

### Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SEC313002D0201 |
| Instructions and Manuals          | 9AKK107492A8855 |

### Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 600 mm |
| Product Net Height | 100 mm |

|                            |         |
|----------------------------|---------|
| Product Net Depth / Length | 335 mm  |
| Product Net Weight         | 5.88 kg |

## Technical

|                                               |                                                                                                                |
|-----------------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Rated Operational Current AC-22B ( $I_e$ )    | (500 V) 160 A                                                                                                  |
| Rated Impulse Withstand Voltage ( $U_{imp}$ ) | 8 kV                                                                                                           |
| Rated Insulation Voltage ( $U_i$ )            | 1 kV                                                                                                           |
| Rated Operational Voltage                     | 500 V AC                                                                                                       |
| Power Loss                                    | at Rated Load 33 W                                                                                             |
| Distance Between Phases                       | 50 mm                                                                                                          |
| Busbar Dimensions                             | Thickness 10 mm                                                                                                |
| Fuse Size                                     | 00                                                                                                             |
| Fuse System                                   | DIN                                                                                                            |
| Operating Mode                                | Motorized                                                                                                      |
| Standards                                     | IEC60947-3                                                                                                     |
| Number of Poles                               | 4                                                                                                              |
| Degree of Protection                          | acc. to IEC 60529 Front IP41                                                                                   |
| Terminal Type                                 | Bolt                                                                                                           |
| Fuse Type                                     | NH                                                                                                             |
| Electronic Fuse Monitoring                    | No                                                                                                             |
| Utilization Category                          | Switching of mixed resistive and inductive loads, including moderate overloads - occasional actuation (AC-22B) |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 1SCC311166D2701 |
| Instructions and Manuals       | 9AKK107492A8855 |
| RoHS Information               | 9AKK107991A2784 |

## Container Information

|                                |             |
|--------------------------------|-------------|
| Package Level 1 Units          | box 1 piece |
| Package Level 1 Width          | 60 mm       |
| Package Level 1 Depth / Length | 340 mm      |
| Package Level 1 Height         | 107 mm      |
| Package Level 1 Gross Weight   | 6.16 kg     |

## Classifications

|        |                                     |
|--------|-------------------------------------|
| ETIM 6 | EC001040 - Fuse switch disconnecter |
|--------|-------------------------------------|

|               |                                                             |
|---------------|-------------------------------------------------------------|
| ETIM 7        | EC001040 - Fuse switch disconnecter                         |
| ETIM 8        | EC001040 - Fuse switch disconnecter                         |
| WEEE Category | 4. Large Equipment (Any External Dimension More Than 50 cm) |

---

**Categories**

---

Low Voltage Products and Systems → Fusegear → Switch Disconnecter Fuse

