

## PRODUCT-DETAILS

# CL2-502G

## Compact LED Pilot Light (CL2-502G)



### General Information

|                       |                                    |
|-----------------------|------------------------------------|
| Extended Product Type | CL2-502G                           |
| Product ID            | 1SFA619403H5022                    |
| EAN                   | 7320500556092                      |
| Catalog Description   | Compact LED Pilot Light (CL2-502G) |
| Long Description      | Compact LED Pilot Light (CL2-502G) |

### Ordering

|                        |           |
|------------------------|-----------|
| Minimum Order Quantity | 100 piece |
| Customs Tariff Number  | 85365019  |

### Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SFC151007C02_  |
| Instructions and Manuals          | 1SFC151011M0201 |

### Dimensions

|                     |         |
|---------------------|---------|
| Product Net Width   | 0.03 m  |
| Product Net Height  | 0.03 m  |
| Product Net Depth / | 0.052 m |

Length

|                    |          |
|--------------------|----------|
| Product Net Weight | 0.018 kg |
|--------------------|----------|

## Technical

|                           |                                                           |
|---------------------------|-----------------------------------------------------------|
| Ambient Air Temperature   | Operation -25 ... +70 °C<br>Storage -40 ... +85 °C        |
| Color                     | Green                                                     |
| Actuator Type             | Pilot light head                                          |
| Illumination              | Illuminated                                               |
| Lamp Type                 | 24V AC / DC, integrated LED                               |
| Degree of Protection      | Front IP66<br>Front IP67<br>Front IP69K<br>Terminals IP20 |
| Enclosure Type NEMA       | Type1<br>Type12<br>Type13<br>Type3R<br>Type4<br>Type4X    |
| Pollution Degree          | 3                                                         |
| Rated Frequency (f)       | Supply Circuit 50 / 60 Hz                                 |
| Rated Operational Voltage | Supply Circuit 24 V AC/DC                                 |
| Terminal Type             | Screw Terminals                                           |
| Tightening Torque         | 0.9 N·m                                                   |
| Wire Stripping Length     | 8 mm                                                      |

## Environmental

|                  |                                                                        |
|------------------|------------------------------------------------------------------------|
| RoHS Status      | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| RoHS Information | 2CMT2015-005451                                                        |
| WEEE Category    | 5. Small Equipment (No External Dimension More Than 50 cm)             |
| WEEE B2C / B2B   | Business To Business                                                   |

## Certificates and Declarations (Document Number)

|                                |                             |
|--------------------------------|-----------------------------|
| CB Certificate                 | CQC_CN_CN50749              |
| cULus Certificate              | UL_E496500-20171020         |
| cURus Certificate              | UL_E496500-20171020         |
| Declaration of Conformity - CE | 2CMT2015-005451             |
| DNV GL Certificate             | 9AKK107046A3749             |
| EAC Certificate                | EAC-RU C-CN.ME77.B.00690_20 |
| Environmental Information      | 1SAC200026H0002             |
| Instructions and Manuals       | 1SFC151011M0201             |
| RoHS Information               | 2CMT2015-005451             |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | bag 100 piece |
| Package Level 1 Width          | 0.125 m       |
| Package Level 1 Depth / Length | 0.235 m       |
| Package Level 1 Height         | 0.05 m        |
| Package Level 1 Gross          | 0.184 kg      |

Weight

|                     |               |
|---------------------|---------------|
| Package Level 1 EAN | 7320500476055 |
|---------------------|---------------|

Classifications

|        |                                     |
|--------|-------------------------------------|
| ETIM 5 | EC000272 - Indicator light complete |
| ETIM 6 | EC000272 - Indicator light complete |
| ETIM 7 | EC000272 - Indicator light complete |
| eClass | V11.0 : 27371223                    |
| UNSPSC | 39121500                            |

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Compact Range → CL

