

## PRODUCT-DETAILS

# CL2-513C

## Compact Pilot Light Clear LED 110-130V AC



### General Information

|                       |                                                                                          |
|-----------------------|------------------------------------------------------------------------------------------|
| Extended Product Type | CL2-513C                                                                                 |
| Product ID            | 1SFA619403R5138                                                                          |
| EAN                   | 7320500556276                                                                            |
| Catalog Description   | Compact Pilot Light Clear LED 110-130V AC                                                |
| Long Description      | Compact Pilot Light - Pilot light head - Clear - Illuminated - Lamptype: LED 110-130V AC |

### Ordering

|                        |            |
|------------------------|------------|
| Minimum Order Quantity | 10 piece   |
| Customs Tariff Number  | 8536619090 |

### Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SFC151007C02_  |
| Instructions and Manuals          | 1SFC151011M0201 |

### Dimensions

|                     |         |
|---------------------|---------|
| Product Net Width   | 0.03 m  |
| Product Net Height  | 0.03 m  |
| Product Net Depth / | 0.052 m |

Length

|                    |          |
|--------------------|----------|
| Product Net Weight | 0.018 kg |
|--------------------|----------|

## Technical

|                           |                                                           |
|---------------------------|-----------------------------------------------------------|
| Ambient Air Temperature   | Operation -25 ... +70 °C<br>Storage -40 ... +85 °C        |
| Color                     | Clear                                                     |
| Actuator Type             | Pilot light head                                          |
| Illumination              | Illuminated                                               |
| Lamp Type                 | 110-13 V AC, integrated LED                               |
| Degree of Protection      | Front IP66<br>Front IP67<br>Front IP69K<br>Terminals IP20 |
| Enclosure Type NEMA       | Type1<br>Type12<br>Type13<br>Type3R<br>Type4<br>Type4X    |
| Pollution Degree          | 3                                                         |
| Rated Frequency (f)       | Supply Circuit 50 / 60 Hz                                 |
| Rated Operational Voltage | Supply Circuit 110 ... 130 V AC                           |
| Terminal Type             | Screw Terminals                                           |
| Tightening Torque         | 0.9 N·m                                                   |
| Wire Stripping Length     | 8 mm                                                      |

## Environmental

|                  |                                                                        |
|------------------|------------------------------------------------------------------------|
| RoHS Status      | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| RoHS Information | 2CMT2015-005451                                                        |
| WEEE Category    | 5. Small Equipment (No External Dimension More Than 50 cm)             |
| WEEE B2C / B2B   | Business To Business                                                   |

## Certificates and Declarations (Document Number)

|                                 |                             |
|---------------------------------|-----------------------------|
| CB Certificate                  | CQC_CN_CN50749              |
| CCC Certificate                 | 2003010305054693_           |
| CQC Certificate                 | CQC2003010305054693         |
| cULus Certificate               | UL_E496500-20171020         |
| cURus Certificate               | UL_E496500-20171020         |
| Declaration of Conformity - CCC | 2020980305001187            |
| Declaration of Conformity - CE  | 2CMT2015-005451             |
| DNV GL Certificate              | 9AKK107046A3749             |
| EAC Certificate                 | EAC-RU C-CN.ME77.B.00690_20 |
| Environmental Information       | 1SAC200026H0002             |
| Instructions and Manuals        | 1SFC151011M0201             |
| RoHS Information                | 2CMT2015-005451             |

## Container Information

|                       |              |
|-----------------------|--------------|
| Package Level 1 Units | bag 10 piece |
| Package Level 1 Width | 0.125 m      |

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Depth / Length | 0.235 m       |
| Package Level 1 Height         | 0.05 m        |
| Package Level 1 Gross Weight   | 0.184 kg      |
| Package Level 1 EAN            | 7320500475676 |

**Classifications**

|                    |                                     |
|--------------------|-------------------------------------|
| ETIM 5             | EC000272 - Indicator light complete |
| ETIM 6             | EC000272 - Indicator light complete |
| ETIM 7             | EC000272 - Indicator light complete |
| eClass             | V11.0 : 27371223                    |
| UNSPSC             | 39121500                            |
| E-Number (Finland) | 2313533                             |
| E-Number (Norway)  | 4373524                             |
| E-Number (Sweden)  | 3705765                             |

**Categories**

Low Voltage Products and Systems → Control Products → Pilot Devices → Compact Range → CL

