

## PRODUCT-DETAILS

# CR-MX220DC2L

CR-MX220DC2L Pluggable interface relay  
2c/o, A1-A2=220VDC, 250V/7A, LED



## General Information

|                       |                                                                                                                                                                                                                                                                                                                                                           |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | CR-MX220DC2L                                                                                                                                                                                                                                                                                                                                              |
| Product ID            | 1SVR405631R9100                                                                                                                                                                                                                                                                                                                                           |
| EAN                   | 4013614535727                                                                                                                                                                                                                                                                                                                                             |
| Catalog Description   | CR-MX220DC2L Pluggable interface relay 2c/o, A1-A2=220VDC, 250V/7A, LED                                                                                                                                                                                                                                                                                   |
| Long Description      | The CR-MX220DC2L pluggable interface relay is from the CR-MX (miniature) relay range. This relay operates with a 220 V DC rated control supply voltage and has a 2 c/o (SPDT) output with contacts rated at 250 V / 7 A. The relay has an integrated LED. Standard sockets, pluggable function modules, holders and markers are available as accessories. |

## Ordering

|                        |           |
|------------------------|-----------|
| Minimum Order Quantity | 300 piece |
| Customs Tariff Number  | 85364900  |

## Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 2CDC117020D0201 |
| Instructions and Manuals          | 1SVC405631M9000 |

## Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 21.5 mm  |
| Product Net Height         | 35 mm    |
| Product Net Depth / Length | 28 mm    |
| Product Net Weight         | 0.034 kg |

## Technical

|                                                |                                           |
|------------------------------------------------|-------------------------------------------|
| Function                                       | Pluggable miniature interface relay CR-MX |
| Sub-Function                                   | Relay with built in LED                   |
| Output                                         | 2 c/o (SPDT) contacts                     |
| Output Signal                                  | 250 V / 7 A                               |
| Rated Control Supply Voltage (U <sub>s</sub> ) | 220 V DC                                  |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| CQC Certificate                | CQC_14002105209 |
| cUR Certificate                | cUR_E244330     |
| Declaration of Conformity - CE | 1SVD982022-0003 |
| Instructions and Manuals       | 1SVC405631M9000 |
| RoHS Information               | 1SVD982022-0002 |
| TÜV Certificate                | TUEV_R50275618  |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | box 10 piece  |
| Package Level 1 Width          | 103 mm        |
| Package Level 1 Height         | 37 mm         |
| Package Level 1 Depth / Length | 142 mm        |
| Package Level 1 Gross Weight   | 0.411 kg      |
| Package Level 1 EAN            | 4013614535734 |
| Package Level 2 Units          | box 300 piece |
| Package Level 2 EAN            | 4013614540325 |

## Classifications

|                            |                            |
|----------------------------|----------------------------|
| Object Classification Code | K                          |
| ETIM 5                     | EC001437 - Switching relay |
| ETIM 6                     | EC001437 - Switching relay |
| ETIM 7                     | EC001437 - Switching relay |
| eClass                     | V11.0 : 27371601           |
| UNSPSC                     | 39122331                   |

---

## Categories

---

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Interface Relays and Optocouplers

