

PRODUCT-DETAILS

CM-MPN.62

CM-MPN.62 Three-phase monitoring relay
2c/o, 0,0.1-30s, L1-L2-L3=3x450-720VAC

"No longer for sale" replaced by



General Information

Extended Product Type	CM-MPN.62
Product ID	1SVR650488R8300
EAN	4013614397585
Catalog Description	CM-MPN.62 Three-phase monitoring relay 2c/o, 0,0.1-30s, L1-L2-L3=3x450-720VAC
Long Description	The CM-MPN.62 is a multifunctional relay from the CM three-phase monitors range. It operates with a rated control supply voltage / three-phase measuring voltage of 450-720 V AC 50/60 Hz and has a 2 c/o (SPDT) output with contacts rated at 250 V / 4 A. This relay monitors all phase parameters such as over/undervoltage, phase unbalance and phase failure. The corresponding threshold values are adjustable. The CM-MPN.62 also offers selection of phase sequence monitoring, automatic phase sequence correction as well as an ON or OFF tripping delay. The output contacts can be configured as 1x2 c/o (SPDT) contacts (common signal) or 2x1 c/o (SPDT) contact (separate signal for over- and undervoltage thresholds) operation. The tripping delay is adjustable over a range of instantaneous to 30 s (0, 0.1-30 s). A sealable transparent cover for protection against unauthorized changes is available as accessory.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900
Replacement Product ID (NEW)	1SVR750488R8300

Popular Downloads

Data Sheet, Technical	2CDC112128D0201
-----------------------	-----------------

Information

Instructions and Manuals	1SVC630530M0000
--------------------------	-----------------

Dimensions

Product Net Width	45 mm
Product Net Depth / Length	100 mm
Product Net Height	78 mm
Product Net Weight	0.22 kg

Technical

Function	Phase failure detection Phase sequence monitoring Automatic phase sequence correction Over- and undervoltage monitoring Phase unbalance detection
Standards	IEC/EN 60255-6 EN 50178
Measuring Range	3x450 ... 720 V AC
Rated Control Supply Voltage (U _s)	3 x 450 ... 720 V AC
Output	2 x 1 c/o or 1 x 2 c/o contacts, configurable
Time Range	200 ms start-up delay 0 s or 0.1 ... 30 s tripping delay (ON or OFF)
Terminal Type	Screw Terminals

Environmental

RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
-------------	---

Certificates and Declarations (Document Number)

CCC Certificate	CCC_2009010303326655
cUL Certificate	cUL508_E140448
Declaration of Conformity - CE	1SAD938501-0133
Environmental Information	1SAA981003-2403
GL Certificate	GL_60286-09HH
Instructions and Manuals	1SVC630530M0000
RMRS Certificate	RMRS_12.04009.250
RoHS Information	1SAA981030-4404
UL Certificate	UL508_E140448

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	81 mm
Package Level 1 Height	106 mm
Package Level 1 Depth / Length	46 mm
Package Level 1 Gross Weight	0.251 kg
Package Level 1 EAN	4013614397585

Classifications

Object Classification	B
Code	
ETIM 4	EC001441 - Phase monitoring relay
ETIM 5	EC001441 - Phase monitoring relay
ETIM 6	EC001441 - Phase monitoring relay
ETIM 7	EC001441 - Phase monitoring relay
eClass	V11.0 : 27371803
UNSPSC	39121536

Categories

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Three Phase Monitors

