

PRODUCT-DETAILS

N2155.9 BL

N2155.9 BL USB connector female



General Information

Extended Product Type	N2155.9 BL
Product ID	2CLA215590N1103
EAN	8427238142975
Catalog Description	N2155.9 BL USB connector female
Long Description	VDI USB outlet female-female BL

Technical

Product Name	USB connector female
Application	USB
Mounting Type	Flush mounted (plaster)
Type of Fastening	Engage (Snap)
Type of Indicator	Without indication field
Surface Finishing	Untreated Glossy
Material	Thermoplastic Plastic
RAL Number	RAL 9010 - Pure White
Color	White
Number of Batteries	0

Environmental

Ambient Air	Operation -5 ... +35 °C
-------------	-------------------------

Temperature	Storage -5 ... +50 °C
Degree of Protection	IP20

Dimensions

Product Net Width	22 mm
Product Net Height	44 mm
Product Net Weight	0.053 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	0.073 m
Package Level 1 Height	0.033 m
Package Level 1 Depth / Length	0.073 m
Package Level 1 Gross Weight	0.053 kg
Package Level 1 EAN	8427238142975

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85369010
Replacement Product ID (NEW)	2CLA215590N1101
Country of Origin	Spain (ES)
Selling Unit of Measure	piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	No declaration needed
Instructions and Manuals	2CLX215509N1001

Popular Downloads

Data Sheet, Technical Information	9AKK10103A5108
Instructions and Manuals	2CLX215509N1001

Classifications

ETIM 6	EC000018 - Insert/cover for communication technology
ETIM 7	EC000018 - Insert/cover for communication technology
ETIM 8	EC000018 - Insert/cover for communication technology
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85369010
UNSPSC	39121406

Categories

Low Voltage Products and Systems → Switch Assortments → Flush Mounted Modular Range - Niessen → Design Zenit → Flush Mounted Inserts with Cover Plate → VDI Connector

Low Voltage Products and Systems → Switch Assortments → VDI - Voice / Data / Image Connectors → VDI Connector → VDI Connector - Flush Mounted → VDI Connector

