

PRODUCT-DETAILS

2260 BM

2260 BM Push dimmer 2M



General Information

Extended Product Type	2260 BM
Product ID	2CLA226000A1003
EAN	8427238036151
Catalog Description	2260 BM Push dimmer 2M
Long Description	230 V~, 50 Hz. 40 - 450 W. 40 - 400 VA. Motors up to 300 VA. With remote control terminal and orientation lamp. Illuminated. Connection and dimension drawing, see appendix.

Technical

Product Name	Push dimmer 2M
Color	Cream white (electro white)
Number of Batteries	0

Environmental

Ambient Air Temperature	Operation -5 ... +35 °C Storage -5 ... +50 °C
-------------------------	--

Dimensions

Product Net Width	44 mm
Product Net Height	44 mm
Product Net Weight	0.132 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	0.076 m
Package Level 1 Height	0.064 m
Package Level 1 Depth / Length	0.076 m
Package Level 1 Gross Weight	0.132 kg
Package Level 1 EAN	8427238036151

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Spain (ES)
Selling Unit of Measure	piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	No declaration needed
Instructions and Manuals	2CLX226009N1001

Popular Downloads

Instructions and Manuals	2CLX226009N1001
--------------------------	-----------------

Classifications

ETIM 6	EC000025 - Dimmer
ETIM 7	EC000025 - Dimmer
ETIM 8	EC000025 - Dimmer
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85369099
UNSPSC	39122206

Categories

Low Voltage Products and Systems → Switch Assortments → Flush Mounted Modular Range - Niessen → Design Status → Flush Mounted Inserts with Cover Plate → Dimmers

Low Voltage Products and Systems → Switch Assortments → Flush Mounted Modular Range - Niessen → Design Stylo → Flush Mounted Inserts with Cover Plate → Dimmers

Low Voltage Products and Systems → Switch Assortments → Light / LoadControl → Electronic Rotary / Push Button Dimmer (all Loads incl. LED, DALI) → Push Button Dimmer - Flush Mounted → Dimmers

