

PRODUCT-DETAILS

AM23886-BG

AM23886-BG BS Single socket outlet 13A, DP switched w/LED - BG



General Information

Extended Product Type	AM23886-BG
Product ID	2CLA623729N3101
EAN	8427238221373
Catalog Description	AM23886-BG BS Single socket outlet 13A, DP switched w/LED - BG
Long Description	Rated voltage: 250Vac Rated current: 13A Double pole Indicator LED Dual earth with child safety shutter system

Technical

Product Name	BS Single socket outlet 13A, DP switched w/LED - BG
Function	BS 1-gang socket outlet 13A, DP sw. w/LED
Material	Glass
Color	Black
Number of Batteries	0

Environmental

Ambient Air Temperature	Operation -5 ... +35 °C Storage -5 ... +50 °C
Environmental Information	9AKK108466A4740

Dimensions

Product Net Width	0.102 mm
Product Net Height	0.062 mm
Product Net Depth / Length	0.102 mm
Product Net Weight	0.083 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	0.102 m
Package Level 1 Height	0.062 m
Package Level 1 Depth / Length	0.102 m
Package Level 1 EAN	8427238221373

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85366990
Country of Origin	Spain (ES)
Selling Unit of Measure	piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	No declaration needed
Environmental Information	9AKK108466A4740
Instructions and Manuals	9AKK106930A7740

Popular Downloads

Data Sheet, Technical Information	9AKK106930A7740
Instructions and Manuals	9AKK106930A7740

Classifications

ETIM 6	EC000125 - Socket outlet
ETIM 7	EC000125 - Socket outlet
ETIM 8	EC000125 - Socket outlet
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85389099

Categories

Low Voltage Products and Systems → Switch Assortments → Flush Mounted Range BS - Niessen → Design Millenium → Flush Mounted Inserts with Cover Plate → Socket Outlets with Advanced Functionality

Low Voltage Products and Systems → Switch Assortments → Socket Outlets → Socket Outlets with Advanced Functionality → Socket Outlets with Advanced Functionality - Flush Mounted → Socket Outlets with Advanced Functionality

