


PRODUCT-DETAILS

8155.91

8155.91 USB female-female connection unit with cable



General Information

Extended Product Type	8155.91
Product ID	2CLA815591A1001
EAN	8427238204093
Catalog Description	8155.91 USB female-female connection unit with cable
Long Description	Front: 1x USB 2.0 connector (Type A connector). Rear: 1x USB 2.0 connector (Type A connector) with 20 cm cable extension. Without fixing claws. Cover plate code: 8555.

Technical

Product Name	USB female-female connection unit with cable
Number of Batteries	0

Environmental

Ambient Air Temperature	Operation -5 ... +35 °C Storage -5 ... +50 °C
-------------------------	--

Dimensions

Product Net Width	74 mm
Product Net Height	74 mm

Product Net Depth / Length	35 mm
Product Net Weight	72 g

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	76 mm
Package Level 1 Height	64 mm
Package Level 1 Depth / Length	76 mm
Package Level 1 Gross Weight	91 g
Package Level 1 EAN	8427238204093

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85369010
Country of Origin	Spain (ES)
Selling Unit of Measure	piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	9AKK106930A1758
Instructions and Manuals	2CLX215509N1001

Popular Downloads

Data Sheet, Technical Information	9AKK107046A0356
Instructions and Manuals	2CLX215509N1001

Classifications

ETIM 6	EC000018 - Insert/cover for communication technology
ETIM 7	EC000018 - Insert/cover for communication technology
ETIM 8	EC000018 - Insert/cover for communication technology
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85369010
UNSPSC	39121406

Categories

Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Niessen → Design Sky → Flush Mounted Inserts → VDI Connector Inserts

Low Voltage Products and Systems → Switch Assortments → VDI - Voice / Data / Image Connectors → VDI Connector → VDI Connector - Flush Mounted → VDI Connector Inserts

