


PRODUCT-DETAILS

8188.3

8188.3 Schuko socket outlet w/ 2 USB-A charger



General Information

Extended Product Type	8188.3
Product ID	2CLA818830A1001
EAN	8427238204741
Catalog Description	8188.3 Schuko socket outlet w/ 2 USB-A charger
Long Description	Schuko® socket outlet: Rated voltage: 250 Vac. +/- 10%; 50/60 Hz. Rated current: 16A. Type F: 2P + E. With child safety shutter Operating temperature: -5° C ... 45 °C
	USB charger: Input current: 0,20 A (with maximum load). Output voltage: 5 Vdc ±5%. Output current: 2.000 mA.
	USB-port Type: Power consumption in stand-by: <= 0,015W@230Vac. Energy efficiency: >= 79%.
	Screw terminals Max. torsion 0.8Nm according to ISO 60884-1 Without fixing claws Cover plate code: 8588.3.

Technical

Product Name	Schuko socket outlet w/ 2 USB-A charger
Rated Voltage (U _r)	220 V

Rated Current (I _n)	15 A
Frequency (f)	50...60 Hz
Number of Phases	2
Number of Gangs	1
Connection Type	Screw
Mounting Type	Flush mounted (plaster)
Socket Outlet Type	Protective Contact (SCHUKO)
Type of Fastening	Engage (Snap)
Legend	Without imprint
Model Number	Protective contact (SCHUKO)
Number of Batteries	0

Environmental

Ambient Air Temperature	Operation -5 ... +35 °C Storage -5 ... +50 °C
Degree of Protection	IP20

Dimensions

Product Net Width	0.149 m
Product Net Height	0.078 m
Product Net Depth / Length	0.225 m
Product Net Weight	0.066 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	0.152 m
Package Level 1 Height	0.078 m
Package Level 1 Depth / Length	0.225 m
Package Level 1 Gross Weight	0.65 kg
Package Level 1 EAN	8427238204741

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85366990
Country of Origin	Spain (ES)
Selling Unit of Measure	piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	9AKK1074920617
Instructions and Manuals	2CLX818839A1001

Popular Downloads

Data Sheet, Technical Information	9AKK107046A0356
Instructions and	2CLX818839A1001

Classifications		
ETIM 6		EC000125 - Socket outlet
ETIM 7		EC000125 - Socket outlet
ETIM 8		EC000125 - Socket outlet
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)	
WEEE B2C / B2B		Business To Consumer
CN8		85365080

Categories
Low Voltage Products and Systems → Switch Assortments → Charging Devices → Charging Devices → Charging Devices - Flush Mounted → Charging Device Inserts
Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Niessen → Design Arco → Flush Mounted Inserts → Charging Device Inserts
Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Niessen → Design Arco → Flush Mounted Inserts → Single Socket Outlet
Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Niessen → Design Olas → Flush Mounted Inserts → Charging Device Inserts
Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Niessen → Design Olas → Flush Mounted Inserts → Single Socket Outlet
Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Niessen → Design Sky → Flush Mounted Inserts → Charging Device Inserts
Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Niessen → Design Sky → Flush Mounted Inserts → Single Socket Outlet
Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Niessen → Design Tacto → Flush Mounted Inserts → Charging Device Inserts
Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Niessen → Design Tacto → Flush Mounted Inserts → Single Socket Outlet
Low Voltage Products and Systems → Switch Assortments → Socket Outlets → Single Socket Outlets → Single Socket Outlets - Flush Mounted → Single Socket Outlet

