


PRODUCT-DETAILS

B8560.2 PL

B8560.2 PL Blister rotatory dimmer LED



General Information

Extended Product Type	B8560.2 PL
Product ID	2CLA856020A1366
EAN	8427238160115
Catalog Description	B8560.2 PL Blister rotatory dimmer LED

Long Description	Blister rotatory dimmer LED
	Color: Silver
	Rated voltage: 230 V~, + 10% / - 10%
	Rated frequency: 50 Hz/60 Hz
	Nominal power: 2 - 100 W/VA (retrofit LED loads).
	Nominal power: 10 - 250 W/VA (non-LED loads).
	With rotary control, 2-way switch and soft-catch.
	2-wire connection (neutral conductor not required)
	Optimised for dimming of retrofit LED lamps (LEDi).
	For dimmable Retrofit-LEDs (LEDi).
	For dimmable Retrofit-LEDs (LEDi) with conventional or electronic transformers.
	For incandescent lamps, 230 V tungsten halogen lamps, low-voltage halogen lamps with conventional or electronic transformers and dimmable energy-saving halogen lamps.
	Mix operation of LEDi with conventional loads possible.
	Via mode switch adjustable between leading edge control and trailing edge control.
	Low-noise level by MOSFET transistors.
	With electronic short-circuit protection. With electronic overload protection.
	With adjustable minimum brightness.
	Temperature range (Device): 0 °C to 35 °C
	In the case of conventional transformers, take ~20% transformer loss into account.
	In case of electronic transformers, 5 % transformer losses.
	Also applicable for 1gang 2way installations.
	Provided with terminal for net disconnection devices.
	Included: fixing claws

Technical

Product Name	Blister rotatory dimmer LED
Rated Voltage (U _r)	230...230 V
Frequency (f)	50...50 Hz
Power Watt	10...250 V-A
Actuator Type	Turn button
Connection Type	Screw
Load Type	Universal and LED Retrofit
Mounting Type	Flush mounted (plaster)
Type of Fastening	Mounting with Claw Mounting with Screw
Surface Finishing	Surface protection: Deco Surface finishing: Matt
Material	Material quality: Thermoplastic Material: Plastic
Color	Silver

Environmental

Ambient Air Temperature	Operation -5 ... +35 °C Storage -5 ... +50 °C
Degree of Protection	IP20

Dimensions

Product Net Width	0.115 m
Product Net Height	0.085 m
Product Net Depth / Length	0.155 m
Product Net Weight	0.132 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	0.115 m
Package Level 1 Height	0.085 m
Package Level 1 Depth / Length	0.155 m
Package Level 1 Gross Weight	0.132 kg
Package Level 1 EAN	8427238160115

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85389099
Country of Origin	Spain (ES)
Selling Unit of Measure	piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	No declaration needed
Instructions and Manuals	2CLX850009A1001

Popular Downloads	
Data Sheet, Technical Information	9AKK107046A0356
Instructions and Manuals	2CLX850009A1001

Classifications	
ETIM 6	EC000025 - Dimmer
ETIM 7	EC000025 - Dimmer
ETIM 8	EC000025 - Dimmer
WEEE Category	Product Not in WEEE Scope

Categories
Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Niessen → Design Sky → CoverPlates (partly incl. Insert) Sky Niessen → Rotary Dimmer
Low Voltage Products and Systems → Switch Assortments → Light / LoadControl → Electronic Rotary / Push Button Dimmer (all Loads incl. LED, DALI) → Rotary Dimmer - Flush Mounted → Rotary Dimmer

