

## PRODUCT-DETAILS

# ABB420MF12W

Mechanical Interlocked Fused 20A 3P4W  
125/250V, UL/CSA approved and CE  
compliant



## General Information

|                       |                                                                                                                                                |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | ABB420MF12W                                                                                                                                    |
| Product ID            | 2CMA100514R1000                                                                                                                                |
| EAN                   | 7392696005142                                                                                                                                  |
| Catalog Description   | Mechanical Interlocked Fused 20A 3P4W 125/250V, UL/CSA approved and CE compliant                                                               |
| Long Description      | Mechanical Interlocked Fused 20A 3P4W 125/250V Clock Position Of Grounding Contact 12 hour Color code Orange, UL/CSA approved and CE compliant |

## Ordering

|                        |                     |
|------------------------|---------------------|
| EAN                    | 7392696005142       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

## Dimensions

|                    |         |
|--------------------|---------|
| Product Net Width  | 160 mm  |
| Product Net Height | 103 mm  |
| Product Net Weight | 1.83 kg |

## Container Information

|                       |        |
|-----------------------|--------|
| Package Level 1 Width | 169 mm |
|-----------------------|--------|



|                        |
|------------------------|
| 339 mm                 |
| 219 mm                 |
| 1.83 kg                |
| 7392696005142          |
| box 1 piece            |
| 800 mm                 |
| 1200 mm                |
| 900 mm                 |
| 96.86 kg               |
| 7392696064347          |
| pallet (lift) 42 piece |
|                        |
|                        |
| Directive 2011/65/EU   |
|                        |
|                        |
| 2CHC660172X0201        |
| CMC700005D0022         |
|                        |
| CMC000057M0000         |
|                        |
| CMC700005D0022         |
| E109667-20021206       |
| CMC700005D0022         |
|                        |
|                        |
|                        |
| 3P+E                   |
| -25 ... 40 °C          |
| 1.5 ... 4 mm²          |
| Other                  |

|                          |                        |
|--------------------------|------------------------|
| Class                    |                        |
| Instructions and Manuals | 2CMC700054M0001        |
| Installation Manual      | 2CMC700052M0001        |
| RAL Number               | RAL 7001 - Silver Grey |

**Classifications**

|        |          |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39120000 |

**Technical**

|                   |                  |
|-------------------|------------------|
| Wire Size         | 14 ... 12 AWG    |
| Tightening Torque | WireClamp0.8 N·m |

**Categories**

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets

