

PRODUCT-DETAILS

ABB432MI3W

Mechanical Interlocked Switch 32A
380V50Hz/440V60Hz, UL/CSA approved and
CE compliant



General Information

Extended Product Type	ABB432MI3W
Product ID	2CMA100671R1000
EAN	7392696006712
Catalog Description	Mechanical Interlocked Switch 32A 380V50Hz/440V60Hz, UL/CSA approved and CE compliant
Long Description	Mechanical Interlocked Switch 32A 380V50Hz/440V60Hz Clock Position Of Grounding Contact 3 hour Color code Red, UL/CSA approved and CE compliant

Ordering

EAN	7392696006712
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	120 mm
Product Net Height	149 mm
Product Net Weight	1.91 kg

Container Information

Package Level 1 Width	115.5 mm
-----------------------	----------

Package Level 1 Depth / Length	142.5 mm
Package Level 1 Height	116 mm
Package Level 1 Gross Weight	1.91 kg
Package Level 1 EAN	7392696006712
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	100.22 kg
Package Level 2 EAN	7392696064873
Package Level 2 Units	pallet (lift) 42 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
SCIP	8022fa0b-e6ff-46ef-a9b3-7a40729f2df1 Czech Republic (CZ)

Certificates and Declarations (Document Number)

CSA Certificate	2CHC660172X0201
Declaration of Conformity - CE	2CMC700005D0022
Environmental Information	2CMC000057M0000
RoHS Information	2CMC700005D0022
UL Certificate	E109667-20021206
REACH Declaration	2CMC700005D0022

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 10 mm ²
Cable Entry Position	Other
Color	Red
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	50/60 Hz
Function	Mechanical Interlock Receptacle
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#ABB432MI3W
Mounting Holes	130x225
Number of Poles	4
Order Multiple	1 piece
Product Main Type	CMVS
Product Name	Switched interlocked socket outlet
Protection Type	Watertight
Rated Current (I _N)	32 A
Rated Voltage (U _r)	380/440 V
Recommended Screw Driver	PH2
Standards	UL 1682, 1686 / CSA C22.2 No. 182.1-13
Suitable for Product	IEC Industrial Plugs and Sockets

Class	
Instructions and Manuals	2CMC700054M0001
Installation Manual	2CMC700054M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440510
UNSPSC	39122205

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets

