

PRODUCT-DETAILS

B24 352-300

B24 352-300 Electricity Meter ; B24 352-300



General Information

Extended Product Type	B24 352-300
Product ID	2CMA100837R1000
EAN	6957625370336
Catalog Description	B24 352-300 Electricity Meter ; B24 352-300
Long Description	Advanced compact DIN-rail meter with an easy to read back lighted display. The meter is intended for use in the commercial or residential buildings etc. The meter can be used in 3 or 4 wire systems. The meter has several instrumentation values, 25 possible alarms and event logs. Three phase transformer connected for active and reactive energy. Import and export of energy in different registers and one total. Resettable register for intermediate values. Up to four tariffs. Two outputs and inputs for pulses or alarm etc. RS-485 communication over Modbus RTU or EQ Bus. Accuracy class 0,5 (or C for MID meters). The meters is IEC approved.

Technical

Standards	standard in conformity with IEC approval
Product Name	Electricity Meter ; B24 352-300
Function	Electricity meter
Sub-Function	Silver
Rated Voltage (U _r)	(Un) N-L 230 ... 240 V (Un) L-L 380 ... 415 V
Rated Current (I _n)	6 A
Current Rating	6 A
Frequency (f)	50/60 Hz
	0.721 W
Communication	Modbus

Interface

Accuracy	Active Energy Class $\pm 0,5\%$ (or C for MID meters). Reactive Energy Class $\pm 2\%$.
Pulse Output Rate	1...999999
Number of Phases	3
Number of Counter Positions	7
Energy Meter Type	Effective Power Blind Power
Meter Type	Transformer connected
Mounting Type	DIN rail
Pulse Output Type	Electrical
Type of Indicator	Digital
Enclosure Material	Plastic
Communication	MODBUS RTU
Model Number	Measurement transformer
Connecting Capacity Main Circuit	0.5 ... 10 mm ²

Environmental

Ambient Air Temperature	Operation -40 ... 70 °C
Degree of Protection	IP20

Dimensions

Width in Number of Modular Spacings	4
Product Net Width	70 mm
Product Net Height	26.5 mm
Product Net Depth / Length	65 mm
Product Net Weight	0.27 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	0.1 m
Package Level 1 Height	0.068 m
Package Level 1 Depth / Length	0.094 m
Package Level 1 Gross Weight	0.35 kg
Package Level 1 EAN	6957625370336

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	90283011
Country of Origin	Italy (IT)
Selling Unit of Measure	piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	No declaration needed
--------------------------------	-----------------------

Instructions and Manuals	2CMC485019M0201
--------------------------	-----------------

Popular Downloads

Data Sheet, Technical Information	2CMC485003M0201
Instructions and Manuals	2CMC485019M0201

Classifications

ETIM 6	EC001506 - Kilowatt-hour meter
ETIM 7	EC001506 - Kilowatt-hour meter
ETIM 8	EC001506 - Kilowatt-hour meter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	90283011
Object Classification Code	P

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Energy Efficiency Devices → Energy Meters

