

PRODUCT-DETAILS

PLV316-12W

Extra low voltage plugs, 3P, 16 A, 40 ... 50 AC V



General Information

Extended Product Type	PLV316-12W
Product ID	2CMA100893R1000
EAN	7392696008938
Catalog Description	Extra low voltage plugs, 3P, 16 A, 40 ... 50 AC V
Long Description	Plug Extra low voltage, secondary key position 12h, rated current 16A, IP67 watertight, 3-poles, frequency 50-60 Hz, color code White

Ordering

EAN	7392696008938
Country of Origin	Austria (AT)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	87 mm
Product Net Height	87 mm
Product Net Weight	0.182 kg

Container Information

Package Level 1 Width	133 mm
Package Level 1 Depth / Length	133 mm
Package Level 1 Height	89 mm
Package Level 1 Gross Weight	1.82 kg
Package Level 1 EAN	7392696009416
Package Level 1 Units	box 10 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1 ... 10 mm²
Cable Diameter	8 ... 24 mm
Cable Entry Position	Anti-kink sleeve
Color	White
Connection Type	Screw
Degree of Protection	IP67
Function	Extra low voltage plug
Housing Material	Plastic
Invoice Description	Ind. P_S#PLV316-12W
Number of Poles	3
Order Multiple	10 piece
Product Main Type	PLV
Product Name	Extra low voltage plug
Protection Type	Watertight
Rated Current (I_n)	16 A
Rated Voltage (U_r)	40 ... 50 V AC
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7001 - Silver Grey

Classifications	
eClass	27440509
UNSPSC	39120000

Categories
Low Voltage Products and Systems → Industrial Plugs and Sockets → Special Plugs & Sockets → Plugs & Sockets for Extra Low Voltage

