PRODUCT-DETAILS

CLV216-12

Industrial Connectors, 2P, 16 A, 40 … 50 AC V

General Information

Extended Product Type	CLV216-12
Product ID	2CMA100902R1000
EAN	7392696009027
Catalog Description	Industrial Connectors, 2P, 16 A, 40 … 50 AC V
Long Description	Connector Extra low voltage, secondary key position 12h, rated current 16A, IP44 splashproof, 2-poles, frequency 50-60 Hz, color code White

Ordering

E-Number (Sweden)	E2417738
EAN	7392696009027
Country of Origin	Austria (AT)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	75 mm
Product Net Height	75 mm
Product Net Weight	0.178 kg

Container Information

Package Level 1 Width	152 mm
Package Level 1 Depth / Length	152 mm
Package Level 1 Height	77 mm
Package Level 1 Gross Weight	1.78 kg
Package Level 1 EAN	7392696009508
Package Level 1 Units	box 10 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	2P
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1 … 10 mm²
Cable Diameter	8 ... 24 mm
Cable Entry Position	Swivel
Color	White
Connection Type	Screw
Degree of Protection	IP44
Function	Extra low voltage connector
Housing Material	Plastic
Invoice Description	Ind. P_S#CLV216-12
Number of Poles	2
Order Multiple	10 piece
Product Main Type	CLV
Product Name	Extra low voltage connector
Protection Type	Splashproof
Rated Current (I_n)	16 A
Rated Voltage (U_r)	40 ... 50 V AC
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440509
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Special Plugs & Sockets → Plugs & Sockets for Extra Low Voltage