

PRODUCT-DETAILS

216RS9B

Surface socket outlets, 2P+E, 16 A, 380 ... 415 V



General Information

Extended Product Type	216RS9B
Product ID	2CMA101052R1000
EAN	7392696010528
Catalog Description	Surface socket outlets, 2P+E, 16 A, 380 ... 415 V
Long Description	Surface socket outlets, 2P+E, IP44, 16 A, 380 ... 415 V

Ordering

EAN	7392696010528
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	66 mm
Product Net Height	91 mm
Product Net Weight	0.240 kg
Mechanical Drawings	9AKK107680A0703

Container Information

Package Level 1 Width	158 mm
Package Level 1 Depth / Length	345 mm
Package Level 1 Height	138 mm
Package Level 1 Gross Weight	2.4 kg
Package Level 1 EAN	7392696014465
Package Level 1 Units	box 10 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	2612 kg
Package Level 2 EAN	7392696065177
Package Level 2 Units	pallet (lift) 1080 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm²
Cable Diameter	18 mm
Cable Entry Position	Cable entry, flexible membrane and metric threaded M20 insert for top cable entry.Rear knock-out cable entry.
Color	Red
Connection Type	Screw
Cover Color	Black
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Outlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P_S#216RS9B

Mounting Holes	75x54
Number of Poles	3
Order Multiple	10 piece
Product Main Type	ERS
Product Name	Wall mounted socket
Protection Type	Splashproof
Rated Current (I _n)	16 A
Rated Voltage (U _r)	380 ... 415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
Installation Manual	2CMC700014C0016
RAL Number	RAL 9005 - Jet Black

Classifications

eClass	27440510
UNSPSC	39120000

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Socket Outlets

