

PRODUCT-DETAILS

416EC9W

Industrial Connectors, 3P+N+E, 16A, 120/208 ... 144/250 V



General Information

Extended Product Type	416EC9W
Product ID	2CMA101138R1000
EAN	7392696011389
Catalog Description	Industrial Connectors, 3P+N+E, 16A, 120/208 ... 144/250 V
Long Description	Industrial Connectors, 3P+N+E, 16A, 120/208 ... 144/250 V Clock Position Of Grounding Contact 9 hour Color code Blue

Ordering

EAN	7392696011389
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	87 mm
Product Net Height	87 mm
Product Net Weight	0.26 kg

Container Information

Package Level 1 Width	355 mm
Package Level 1 Depth / Length	165 mm
Package Level 1 Height	170 mm
Package Level 1 Gross Weight	2.6 kg
Package Level 1 EAN	7392696018609
Package Level 1 Units	box 10 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	1840 kg
Package Level 2 EAN	7392696065474
Package Level 2 Units	pallet (lift) 700 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CB Certificate	2CHC660164X0201
Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1620515
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1 ... 2.5 mm²
Cable Diameter	17 mm
Cable Entry Position	Swivel
Color	Blue
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Connector
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#416EC9W
Number of Poles	5

Order Multiple	10 piece
Product Main Type	EC
Product Name	Industrial Connector
Protection Type	Watertight
Rated Current (I_n)	16 A
Rated Voltage (U_r)	120/208 ... 144/250 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7012 - Basalt Grey

Classifications

eClass	27440509
UNSPSC	39120000

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Connectors

